

Section 1: IDENTIFICATION

1.1 PRODUCT IDENTIFIER

Product Name: SKD-S2
Product Code: Not available.

1.2 RECOMMENDED USE OF CHEMICAL AND RESTRICTIONS ON USE

Use: Non-Destructive Testing.

1.3 DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEET

Name/Address: Magnaflux

155 Harlem Avenue, Glenview, Illinois

60025

Telephone Number: 847-657-5300

1.4 EMERGENCY TELEPHONE NUMBER

Emergency Telephone Number: CHEMTREC 800-424-9300

Date of Preparation: November 25, 2013 Version #: 1.1

Section 2: HAZARD(S) IDENTIFICATION

2.1 CLASSIFICATION OF THE CHEMICAL ACCORDING TO OSHA HAZCOM 2012

Hazard class

Flammable Liquid 2 Eye irritation 2A

Specific target organ toxicity - Single exposure 3 Specific target organ toxicity - Repeated exposure 1

2.2 LABEL ELEMENTS ACCORDING TO OSHA HAZCOM 2012

Hazard Pictogram:







Signal Word: Danger

Hazard Statement: Highly flammable liquid and vapor. Causes serious eye irritation.

May cause drowsiness or dizziness. Causes damage to lungs

through prolonged or repeated exposure.

Prevention: Keep away from heat/sparks/open flames/hot surfaces. – No

smoking. Keep container tightly closed. Ground/Bond container and receiving equipment. Use explosion-proof electrical/ventilating/

lighting equipment. Use only non-sparking tools. Take

precautionary measures against static discharge. Wear protective

Page 1 of 10

Trade Name: SKD-S2



gloves/eye protection/face protection. Wash hands thoroughly after

handling. Use only outdoors or in a well-ventilated area. Do not breathe dust/fume/gas/mist/vapors/spray. Do not eat, drink or

smoke when using this product.

Response: If on skin (or hair): Take off immediately all contaminated clothing.

Rinse skin with water/shower. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If inhaled: Remove person to fresh air and keep comfortable for

breathing. Call a poison center/doctor if you feel unwell.

Storage: Store in a well-ventilated place. Keep container tightly closed. Store

locked up. Keep cool.

Disposal: Dispose of contents and container in accordance with all local,

regional, national and international regulations.

2.3 ADDITIONAL INFORMATION

Hazards not otherwise classified: Not applicable.

11 % of the mixture consists of ingredient(s) of unknown acute toxicity.

This product is a hazardous chemical as defined by NOM-018-STPS-2000.

Mexico Classification:



Blue = Health Red = Flammability Yellow = Reactivity White = Special

Hazard Rating: 0 = minimal, 1 = slight, 2 = moderate, 3 = severe, 4 = extreme

WHMIS Classification(s):

Class B2 - Flammable Liquid Class D2A - Chronic Toxic Effects

Class D2B - Eye Irritant

WHMIS Hazard Symbols:





WHMIS Signal Word: DANGER

Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 MIXTURES

Page 2 of 10

Conforms to OSA HazCom 2012, CPR & NOM-018-STPS-2000 Standards



Ingredient	UN#	H/F/R/*	CAS No	Wt. %
Isopropanol	UN1219	1/3/0	67-63-0	40 - 70
Acetone	UN1090	1/3/0	67-64-1	10 - 30
Ceramic materials and wares, chemicals	Not available.	Not available.	66402-68-4	5 - 10
Talc	Not available.	Not available.	14807-96-6	1 - 5
Silica, crystalline, quartz	Not available.	Not available.	14808-60-7	< 0.1

The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

Section 4: FIRST- AID MEASURES

4.1 DESCRIPTION OF THE FIRST AID MEASURE

Eye: In case of contact, immediately flush eyes with plenty of water for at

least 15 minutes, including under lids. If easy to do, remove contact

lenses, if worn. Get medical attention immediately.

Skin: In case of contact, immediately flush skin with plenty of water. Call a

physician if irritation develops and persists.

Inhalation: If breathing is difficult, remove to fresh air and keep at rest in a position

comfortable for breathing. Get medical advice/attention if you feel unwell.

Ingestion: If swallowed, do NOT induce vomiting unless directed to do so by

medical personnel. Never give anything by mouth to an unconscious

person. Get immediate medical advice/attention.

4.2 MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED

Eye: Causes serious eye irritation. Symptoms may include discomfort or

pain, excess blinking and tear production, with marked redness and

swelling of the conjunctiva.

Skin: May cause skin irritation. Symptoms may include redness, drying,

defatting and cracking of the skin.

Inhalation: May cause respiratory tract irritation. May cause drowsiness or

dizziness.

Ingestion: May be harmful if swallowed. May cause stomach distress, nausea

or vomiting.

4.3 INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENTS NEEDED

Note to Physicians: Symptoms may not appear immediately.

Specific Treatments: In case of accident or if you feel unwell, seek medical advice

immediately (show the label or SDS where possible).

Section 5: FIRE-FIGHTING MEASURES

5.1 FLAMMABILITY

Flammability: Flammable by WHMIS/OSHA/NOM-018-STPS-2000 criteria.

^{*} Per NOM-018-STPS-2000



5.2 EXTINGUISHING MEDIA

Suitable Extinguishing Media: Water, foam, carbon dioxide.

Unsuitable Extinguishing Media: Not available.

5.3 SPECIAL HAZARDS ARISING FROM THE CHEMICAL

Products of Combustion: May include, and are not limited to: oxides of carbon.

Explosion Data:

Sensitivity to Mechanical Impact: Not available.
Sensitivity to Static Discharge: Not available.

5.4 SPECIAL PROTECTIVE EQUIPMENT AND PRECAUTIONS FOR FIRE FIGHTERS

Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA). Use water spray to keep fire-exposed containers cool.

Section 6: ACCIDENTAL RELEASE MEASURES

6.1 PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES

Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Eliminate sources of ignition.

6.2 METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING - UP

Methods for Containment: Contain and/or absorb spill with inert material (e.g. sand, vermiculite),

then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).

Methods for Cleaning-Up: Scoop up material and place in a disposal container. Provide ventilation.

Section 7: HANDLING AND STORAGE

7.1 PRECAUTIONS FOR SAFE HANDLING

Handling: Keep away from heat/sparks/open flames/hot surfaces. - No

smoking. Avoid contact with skin and eyes. Do not breathe

dust/fume/gas/mist /vapors/spray. Do not swallow. Handle and open container with care. Use only outdoors or in a well-ventilated area. When using do not eat, drink or smoke. Use only non-sparking tools.

(See section 8)

General Hygiene Advice: Launder contaminated clothing before reuse. Wash hands before

eating, drinking, or smoking.

7.2 CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES

Storage: Keep out of the reach of children. Keep container tightly closed.

Store in a cool, well ventilated area. Keep away from sources of

ignition. Store locked up. (See section 10)

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION



8.1 CONTROL PARAMETERS

Exposure Guidelines

Occupational Exposure Limits			
Ingredient	OSHA-PEL	ACGIH-TLV	
Isopropanol	400 ppm	200 ppm	
Acetone	1000 ppm TWA; 2400 mg/m ³ TWA	500 ppm	
Ceramic materials and wares, chemicals	5 mg/m ³	Not available.	
Talc	20 mppcf	2 mg/m ³ (resp)	
	$((10 \text{ mg/m}^3)/(\%\text{SiO}_2+2) \text{ TWA (resp)})$ $((30 \text{ mg/m}^3)/(\%\text{SiO}_2+2) \text{ TWA (total)})$		
	$((30 \text{ mg/m}^3)/(\% \text{SiO}_2 + 2) \text{ TWA (total)})$		
Silica, crystalline, quartz	$((250)/(\%SiO_2+5) \text{ mppcf TWA (resp)})$	0.025 mg/m ³	

8.2 EXPOSURE CONTROLS

Engineering Controls: Use ventilation adequate to keep exposures (airborne levels of dust,

fume, vapor, etc.) below recommended exposure limits.

8.3 INDIVIDUAL PROTECTIVE MEASURES

Personal Protective Equipment:

Eye/Face Protection: Safety glasses or goggles are recommended when using product.

Skin Protection:

Hand Protection: Chemical-resistant gloves.

Body Protection: Wear suitable protective clothing.

Respiratory Protection: In case of insufficient ventilation, wear suitable respiratory equipment.

Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the

selected respirator.

General Health and Safety

Measures:

Do not eat, smoke or drink where material is handled, processed or stored. Wash hands carefully before eating or smoking. Handle according to established industrial hygiene and safety practices.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES

Appearance: White liquid.

Color: White.
Odor: Alcohol.

Odor Threshold: Not available.

Physical State: Liquid. pH: Neutral.

Melting Point/Freezing Point: Not available.

Initial Boiling Point and Boiling Range: ~ 55 °C (~ 132 °F)



Flash Point: $\sim -16 \, ^{\circ}\text{C} \, (\sim 2 \, ^{\circ}\text{F})$ Evaporation Rate: $0.4 \, (\text{Ether} = 1)$ Flammability: Flammable.

Lower Flammability/Explosive Limit: 2 %
Upper Flammability/Explosive Limit: 15 %

Vapor Pressure: 150 mm @ 38°C (100 °F)

Vapor Density: 3

Relative Density/Specific Gravity: 0.87

Solubility: Partial.

Partition coefficient: n-octanol/water:

Auto-ignition Temperature:

Decomposition Temperature:

Viscosity:

Oxidizing Properties:

Not available.

Not available.

Not available.

Not available.

Section 10: STABILITY AND REACTIVITY

10.1 REACTIVITY

No dangerous reaction known under conditions of normal use.

10.2 CHEMICAL STABILITY

Stable under normal storage conditions.

10.3 POSSIBILITY OF HAZARDOUS REACTIONS

No dangerous reaction known under conditions of normal use.

10.4 CONDITIONS TO AVOID

Heat. Incompatible materials. Sources of ignition.

10.5 INCOMPATIBLE MATERIALS

Strong oxidizing agents.

10.6 HAZARDOUS DECOMPOSITION PRODUCTS

May include, and are not limited to: oxides of carbon.

Section 11: TOXICOLOGICAL INFORMATION

11.1 INFORMATION ON TOXICOLOGICAL EFFECTS

Likely Routes of Exposure: Skin contact, eye contact, inhalation, and ingestion.

Symptoms related to physical/chemical/toxicological characteristics:

Eye: Causes serious eye irritation. Symptoms may include discomfort or pain,

Page 6 of 10



excess blinking and tear production, with marked redness and swelling of

the conjunctiva.

Skin: May cause skin irritation. Symptoms may include redness, drying,

defatting and cracking of the skin.

Ingestion: May be harmful if swallowed. May cause stomach distress, nausea or

vomiting.

Inhalation: May cause respiratory tract irritation. May cause drowsiness or dizziness.

Acute Toxicity:

Ingredient	IDLH	LC50	LD50
			Oral 4396 mg/kg, rat
		Inhalation 72.6	Dermal 12800 mg/kg, rat
Isopropanol	2,000 ppm	mg/L 4h, rat	Dermal 12870 mg/kg, rabbit
		Inhalation 50100	3 3:
Acetone	2,500 ppm	mg/m ³ 8h, rat	Oral 5800 mg/kg, rat
Ceramic materials			Oral > 2000 mg/kg, rat
and wares, chemicals	Not available.	Not available.	Dermal > 2500 mg/kg, rabbit
Talc	1,000 mg/m ³	Not available.	Not available.
	25 mg/m ³ (Cristobalite &		
Silica, crystalline,	Tridymite)		
quartz	50 mg/m³ (Quartz & Tripoli)	Not available.	Oral 500 mg/kg, rat

Calculated overall Chemical Acute Toxicity Values			
LC50 (inhalation) LD50 (oral) LD50 (dermal)			
> 20 mg/L 4h, rat > 2000 mg/kg, rat > 2000 mg/kg, rabbit			

Ingredient	Chemical Listed as Carcinogen or Potential Carcinogen (NTP, IARC, OSHA, ACGIH, CP65)*
Isopropanol	G-A4, I-3
Acetone	G-A4
Ceramic materials and wares, chemicals	Not listed.
Talc	G-A4, I-3
Silica, crystalline, quartz	G-A2, I-1, N-1, O, CP65

^{*} See Section 15 for more information.

11.2 DELAYED, IMMEDIATE, AND CHRONIC EFFECTS OF SHORT- AND LONG-TERM EXPOSURE

Skin Corrosion/Irritation: Based on available data, the classification criteria are not met.

Serious Eye Damage/Irritation: Causes serious eye irritation.

Respiratory Sensitization: Based on available data, the classification criteria are not met. **Skin Sensitization:** Based on available data, the classification criteria are not met.

STOT-Single Exposure: May cause drowsiness or dizziness.

Chronic Health Effects:

Carcinogenicity: Based on available data, the classification criteria are not met.



Germ Cell Mutagenicity: Based on available data, the classification criteria are not met.

Reproductive Toxicity:

Developmental: Based on available data, the classification criteria are not met.

Teratogenicity: Based on available data, the classification criteria are not met. **Embryotoxicity:** Based on available data, the classification criteria are not met.

Fertility: Based on available data, the classification criteria are not met.

STOT-Repeated Exposure: Causes damage to lungs through prolonged or repeated exposure.

Aspiration Hazard: Based on available data, the classification criteria are not met.

Toxicologically Synergistic

Materials:Not available.Other Information:Not available.

Section 12: ECOLOGICAL INFORMATION

12.1 ECOTOXICITY

Acute/Chronic Toxicity: May cause long-term adverse effects in the aquatic environment.

12.2 PERSISTENCE AND DEGRADABILITY

Not available.

12.3 BIOACCUMULATIVE POTENTIAL

Bioaccumulation: Not available.

12.4 MOBILITY IN SOIL

Not available.

12.5 OTHER ADVERSE EFFECTS

Not available.

Section 13: DISPOSAL CONSIDERATIONS

13.1 WASTE TREATMENT METHODS

Disposal Method: This material must be disposed of in accordance with all

local, state, provincial, and federal regulations.

Other disposal recommendations: Not available.

Section 14: TRANSPORT INFORMATION

DOT	UN 1993, Flammable Liquid, n.o.s. (Isopropanol, acetone), 3, II
IATA	UN 1993, Flammable liquid, n.o.s., (Isopropanol, Acetone),3, II (CAO)
IMDG	UN 1993, Flammable Liquid, n.o.s. (Isopropanol, acetone), 3, II (non-bulk)

Section 15: REGULATORY INFORMATION



15.1 SAFETY, HEALTH AND ENVIRONMENTAL REGULATIONS/ LEGISLATIONS SPECIFIC FOR THE CHEMICAL

Canada: This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

US: MSDS prepared pursuant to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Mexico: MSDS prepared pursuant to NOM-018-STPS-2000.

SARA Title III				
Ingredient	Section 302 (EHS) TPQ (lbs.)	Section 304 EHS RQ (lbs.)	CERCLA RQ (lbs.)	Section 313
Isopropanol	Not listed.	Not listed.	Not listed.	313
Acetone	Not listed.	Not listed.	5,000	Not listed.
Ceramic materials and wares,				
chemicals	Not listed.	Not listed.	Not listed.	Not listed.
Talc	Not listed.	Not listed.	Not listed.	Not listed.
Silica, crystalline, quartz	Not listed.	Not listed.	Not listed.	Not listed.

State Regulations

California Proposition 65:

This product contains a chemical known to the State of California to cause cancer.

Global Inventories:

Ingredient	Canada DSL/NDSL	USA TSCA
Isopropanol	DSL	Yes.
Acetone	DSL	Yes.
Ceramic materials and wares, chemicals	DSL	Yes.
Talc	DSL	Yes.
Silica, crystalline, quartz	DSL	Yes.

NFPA-National Fire Protection Association:		
Health: 2		
Fire: 3		
Reactivity: 0		

HMIS-Hazardous Materials Identification System:		
Health: 2*		
Fire: 3		
Physical Hazard: 0		

Hazard Rating: 0 = minimal, 1 = slight, 2 = moderate, 3 = severe, 4 = extreme

SOURCE AGENCY CARCINOGEN CLASSIFICATIONS:

CP65 California Proposition 65

Page 9 of 10

Trade Name: SKD-S2



OSHA (O) Occupational Safety and Health Administration.

ACGIH (G) American Conference of Governmental Industrial Hygienists.

A1 - Confirmed human carcinogen.

A2 - Suspected human carcinogen.

A3 - Animal carcinogen.

A4 - Not classifiable as a human carcinogen. A5 - Not suspected as a human carcinogen.

IARC (I) International Agency for Research on Cancer.

1 - The agent (mixture) is carcinogenic to humans.

2A - The agent (mixture) is probably carcinogenic to humans; there is limited evidence of carcinogenicity in humans and sufficient evidence of carcinogenicity in experimental animals.

2B - The agent (mixture) is possibly carcinogenic to humans; there is limited evidence of carcinogenicity in humans in the absence of sufficient evidence of carcinogenicity in experimental animals.

3 - The agent (mixture, exposure circumstance) is not classifiable as to its carcinogenicity to humans.

4 - The agent (mixture, exposure circumstance) is probably not carcinogenic to humans.

NTP (N) National Toxicology Program.

1 - Known to be carcinogens.

2 - Reasonably anticipated to be carcinogens.

Section 16: OTHER INFORMATION

Date of Preparation: November 25, 2013

Expiry Date: November 25, 2016

Version: 1.1

Revision Date: June 9, 2015

Conforms to OSHA HazCom 2012, CPR & NOM-018-STPS-2000 Standards

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.

Prepared by: Nexreg Compliance Inc.

Phone: (519) 488-5126

www.nexreg.com

Prepared for: Magnaflux

End of Safety Data Sheet

Page 10 of 10

Trade Name: SKD-S2