

# Safety Data Sheet

Version 2

# 1. Identification of the Substance/Preparation and of the Company/Undertaking

<u>Product Identifier</u> Product name Chemical name	CHAMPION SPRAYON SPRAY SCENTS METERED AIR FRESHENER WARM HARVEST 7-8181
<u>Other means of identification</u> Product code Synonyms	FG 438-5310-5 Metered Air Freshener
Recommended use of the chemical	and restrictions on use
Recommended Use	Room Deodorizer.
Uses advised against	Do not spray on varnished, painted or plastic surfaces.
Details of the supplier of the safety	data sheet
Supplier Address	Manufacturer Address
Chase Products Co.	Chase Products Co.
2727 Gardner Road	2727 Gardner Road
Broadview, IL 60155	Broadview, IL 60155
708-865-1000	708-865-1000
Emergency Telephone Number Company Phone Number 24 Hour Emergency Phone Number	708-865-1000 1-800-255-3924

# 2. Hazards Identification

## **Classification**

Acute toxicity - Inhalation (Gases)	Category 4
Serious eye damage/eye irritation	Category 2
Specific target organ toxicity (single exposure)	Category 3
FLAMMABLE AEROSOLS	Category 1
Gases Under Pressure	liquefied gas

## Label Elements

## **EMERGENCY OVERVIEW**

## DANGER

hazard statements HARMFUL IF INHALED Causes serious eye irritation May cause drowsiness or dizziness EXTREMELY FLAMMABLE AEROSOL Contains gas under pressure; may explode if heated



Appearance Clear liquid that will be	Physical State Aerosol	Odor Perfumed.
aerosolized.		

## **Precautionary Statements - Prevention**

ı.

Avoid breathing fumes, mist, vapors or spray. Use only outdoors or in a well-ventilated area Wash face, hands and any exposed skin thoroughly after handling Wear protective gloves, protective clothing, eye protection and face protection. Keep away from heat, sparks, open flames and hot surfaces. — No smoking Pressurized container: Do not pierce or burn, even after use Do not spray on an open flame or other ignition source

#### **Precautionary Statements - Response**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing Call a POISON CENTER or doctor if you feel unwell

#### **Precautionary Statements - Storage**

Store in a well-ventilated place. Keep container tightly closed Store locked up Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

#### Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

#### Hazards not otherwise classified (HNOC)

Other Information

• MAY BE HARMFUL IF SWALLOWED

Harmful to aquatic life with long lasting effects

· Harmful to aquatic life

0% of this mixture consist of ingredient(s) of unknown toxicity.

## 3. Composition/information on Ingredients

Synonyms	
Chemical Family	
Formula	

Metered Air Freshener. MIXTURES. 7-8169

Chemical name	CAS No	weight-%	Trade secret
Acetone	67-64-1	25-30	*
Diethylene Glycol Monoethyl Ether	111-90-0	20-25	*
N-Butane	106-97-8	15-20	*
1,1-Difluoroethane	75-37-6	10-15	*
Propane	74-98-6	5-10	*
Petroleum distillates, hydrotreated light	64742-47-8	1-5	*

\* The exact percentage (concentration) of composition has been withheld as a trade secret.

## 4. First aid measures

## FIRST AID MEASURES

Eye Contact	Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control center or doctor for treatment advice.
Skin contact	In case of contact, immediately flush skin with plenty of water. Wash skin with soap and water. If irritation develops, consult a physician.

Inhalation	If overcome by vapor, move person to fresh air. If person is not breathing, call 911 or an ambulance, then provide artifical respiration, preferably mouth-to-mouth, if possible. Call a poison control center or doctor for further treatment advise.	
Ingestion	Ingestion from an aerosol product is unlikely to occur. Contains petroleum distillates. Harmful if swallowed. If accidentally swallowed, do not induce vomiting, call physician immediately.	
Most important symptoms and effects, both acute and delayed		
Symptoms	Acute: Prolonged inhalation of concentrated vapor or mist may cause headaches, dizziness and nausea. Prolonged and repeated contact with skin may cause irritation and reddening. Contact with eyes causes irritation.	
Indication of any immediate medical attention and special treatment needed		
Note to physicians	Treat symptomatically.	
5. Fire-fighting measures		

#### Suitable extinguishing media

Dry chemical, CO2 or water spray.

Unsuitable extinguishing media Caution: Use of water spray when fighting fire may be inefficient.

# Specific hazards arising from the chemical

This product is under pressure. Water spray may be used to cool cans in the vicinity of fire or excessive heat to prevent the explosion of the cans.

Hazardous combustion products Thermal decomposition may yield gases like carbon monoxide, carbon dioxide, hydrofluoric acid and carbonyl halides.

#### Explosion data

Sensitivity to Mechanical Impact	Contents are under pressure. Handle an extremely flammable material. Follow label
	directions for correct installation and placement of dispenser. Store cans in a cool, dry place
	away from heat and open flame.
Sensitivity to Static Discharge	Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric
-	motors and static electricity).

## Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

#### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures		
Personal precautions	Use with adequate general or local exhaust ventilation.	
For emergency responders	Remove all sources of ignition.	
Environmental precautions		
Environmental precautions	See Section 12 for additional Ecological Information.	
Methods and material for containment and cleaning up		
Methods for Containment	Provide adequate ventilation to area being treated. Soak up spills with chemically inert, absorbent material.	
Methods for cleaning up	Clean contaminated surface thoroughly.	

# 7. Handling and Storage

## Precautions for safe handling

Advice on safe handling	Handle as an extremely flammable material. Follow label directions for correct installation and placement of dispenser. Store cans in a cool, dry place away from heat and open flame.	
Conditions for safe storage, including any incompatibilities		
Storage Conditions	Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). <b>AEROSOL STORAGE LEVEL III (NFPA-30B).</b>	
Incompatible Materials	Avoid heat, open flame and contact with strong oxidizers, inorganic acids and halogens.	
8. Exposure Controls/Personal Protection		

#### Control parameters

**Exposure guidelines** 

See occupational exposure limits listed below.

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Acetone	STEL: 500 ppm	TWA: 1000 ppm	IDLH: 2500 ppm
67-64-1	TWA: 250 ppm	TWA: 2400 mg/m <sup>3</sup>	TWA: 250 ppm
		(vacated) TWA: 750 ppm	TWA: 590 mg/m <sup>3</sup>
		(vacated) TWA: 1800 mg/m <sup>3</sup>	
		(vacated) STEL: 2400 mg/m <sup>3</sup>	
		The acetone STEL does not	
		apply to the cellulose acetate	
		fiber industry. It is in effect for all	
		other sectors.	
		(vacated) STEL: 1000 ppm	
N-Butane	STEL: 1000 ppm explosion	(vacated) TWA: 800 ppm	IDLH: 1600 ppm
106-97-8	hazard	(vacated) TWA: 1900 mg/m <sup>3</sup>	TWA: 800 ppm
			TWA: 1900 mg/m <sup>3</sup>
Propane	: See Appendix F: Minimal	TWA: 1000 ppm	IDLH: 2100 ppm
74-98-6	Oxygen Content, explosion	TWA: 1800 mg/m <sup>3</sup>	TWA: 1000 ppm
	hazard	(vacated) TWA: 1000 ppm	TWA: 1800 mg/m <sup>3</sup>
		(vacated) TWA: 1800 mg/m <sup>3</sup>	

#### Appropriate engineering controls

**Engineering controls** 

Use with adequate general or local exhaust ventilation.

#### Individual protection measures, such as personal protective equipment

Eye/face Protection	Conventional eyeglasses to guard against splashing.
Skin and Body Protection	Household type gloves.
Respiratory protection	Use in a well-ventilated area ONLY. None required if used in a well-ventilated area. Follow label directions for correct use of the product
General hygiene considerations	Wash hands thoroughly after handling.

# 9. Physical and Chemical Properties

## Information on basic physical and chemical properties

Physical State Appearance	Aerosol Clear liquid that will be aerosolized.	Odor	Perfumed.
Color	Color will vary depending on the perfume in the product.	Odor threshold	No information available

<u>Property</u> pH Melting point/freezing point Boiling point/boiling range Flash Point	<u>Values</u> Not applicable Not applicable Acetone 133 F/56.29 C This is an aerosol product for which Flame Projection is 12-14 inches without flashback. Temperatures above 120 F may cause cans to burst.	Remarks • Method Solvent-based product. No information available No information available No information available
Evaporation Rate Flammability (solid, gas) Flammability Limits in Air	Faster than butyl acetate	No information available No information available No information available
Upper flammability limits Lower Flammability Limit	Not available Not available	
Vapor pressure Vapor Density Relative Density Water solubility Solubility in other solvents Partition coefficient Autoignition Temperature Decomposition temperature Kinematic viscosity Dynamic viscosity	0.86 g/ml Insoluble in water	No information available No information available
Explosive properties Oxidizing properties	No information available No information available	
Other Information		
Softening point Molecular weight VOC content (%) Density Bulk Density	No information available No information available 29.63% 7.16 lb/gal No information available	

# 10. Stability and Reactivity

Reactivity Not applicable

No data available

Chemical stability Stable.

<u>Possibility of hazardous reactions</u> Temperatures above 130 °F may cause cans to burst with force.

#### hazardous polymerization

Hazardous polymerization does not occur.

## Conditions to Avoid Temperatures above 122 °F (50 °C).

Incompatible Materials

Avoid heat, open flame and contact with strong oxidizers, inorganic acids and halogens.

## Hazardous decomposition products

Thermal decomposition may yield gases like carbon monoxide, carbon dioxide, hydrofluoric acid and carbonyl halides.

## **11. Toxicological Information**

## Information on likely routes of exposure

## FG 438-5310-5 CHAMPION SPRAYON SPRAY SCENTS METERED AIR FRESHENER WARM HARVEST

Product Information	This product has not been	tested as whole. See below for	information on ingredients.
Inhalation	No data available.		
Eye Contact	No data available.		
Skin contact	No data available.		
Ingestion	No data available.		
Chemical name	Oral LD50	dermal LD50	Inhalation LC50

Chemical name	Oral LD50	dermal LD50	Inhalation LC50
Acetone	= 5800 mg/kg (Rat)	> 15700 mg/kg (Rabbit)	= 50100 mg/m³(Rat)8 h
67-64-1			
Diethylene Glycol Monoethyl Ether	= 10502 mg/kg (Rat)	= 4200 µL/kg (Rabbit) = 6 mL/kg (	> 5240 mg/m³ (Rat)4 h
111-90-0		Rat ) = 9143 mg/kg (Rabbit)	
N-Butane	-	-	= 658 g/m³ (Rat)4 h
106-97-8			
Propane	-	-	> 800000 ppm (Rat)15 min
74-98-6			
Petroleum distillates, hydrotreated	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 5.2 mg/L (Rat)4 h
light			
64742-47-8			

## Information on toxicological effects

Symptoms

Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

## Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Serious eye damage/eye irritation irritation corrosivity sensitization Germ cell mutagenicity Carcinogenicity	May cause skin irritation and reddening after prolonged or repeated contact with skin. Irritating to eyes. May cause skin and eye irritation. Not applicable. No information available. No information available. Not known chronic effects based on available data. None of the ingredients present in excess of 0.1% are listed as carcinogenic by NTP, IARC or OSHA.
---	--

Reproductive toxicity	No information available.
STOT - single exposure	No information available.
STOT - repeated exposure	No information available.
Aspiration Hazard	No information available.

#### Numerical measures of toxicity - Product Information

Unknown acute toxicity	0% of this mixture consist of ingredient(s) of unknown toxicity.
The following values are calculated	based on chapter 3.1 of the GHS document
ATEmix (oral)	4755 mg/kg
ATEmix (dermal)	31248 mg/kg
ATEmix (inhalation-gas)	10804 mg/l
ATEmix (inhalation-dust/mist)	15 mg/l
ATEmix (inhalation-vapor)	78 mg/l

# **12. Ecological Information**

## ecotoxicity

6.1 % of the mixture consists of components(s) of unknown hazards to the aquatic environment

Chemical name	Algae/aquatic plants	Fish	Toxicity to Microorganisms	Crustacea
Acetone		6210 - 8120: 96 h	EC50 = 14500 mg/L 15 min	10294 - 17704: 48 h

## FG 438-5310-5 CHAMPION SPRAYON SPRAY SCENTS METERED AIR FRESHENER WARM HARVEST

67-64-1	Pimephales promelas mg/L	Daphnia magna mg/L EC50
	LC50 static 8300: 96 h	Static 12600 - 12700: 48 h
	Lepomis macrochirus mg/L	Daphnia magna mg/L EC50
	LC50 4.74 - 6.33: 96 h	
	Oncorhynchus mykiss mL/L	
	LC50	
Diethylene Glycol Monoethyl	19100 - 23900: 96 h	3940 - 4670: 48 h Daphnia
Ether	Lepomis macrochirus mg/L	magna mg/L EC50
111-90-0	LC50 flow-through 13400:	5 5
	96 h Salmo gairdneri mg/L	
	LC50 flow-through 10000:	
	96 h Lepomis macrochirus	
	mg/L LC50 static 11400 -	
	15700: 96 h Oncorhynchus	
	mykiss mg/L LC50	
	flow-through 11600 - 16700:	
	96 h Pimephales promelas	
	mg/L LC50 flow-through	
Petroleum distillates,	2.2: 96 h Lepomis	4720: 96 h Den-dronereides
hydrotreated light	macrochirus mg/L LC50	heteropoda mg/L LC50
64742-47-8	static 45: 96 h Pimephales	······································
	promelas mg/L LC50	
	flow-through 2.4: 96 h	
	Oncorhynchus mykiss mg/L	

## Persistence and degradability

No information available.

#### **Bioaccumulation**

No information available.

Chemical name	Partition coefficient
Acetone	-0.24
67-64-1	0.0
Diethylene Glycol Monoethyl Ether 111-90-0	-0.8
N-Butane 106-97-8	2.89
Propane	2.3
74-98-6	

Other adverse effects

No information available

## **13. Disposal Considerations**

## Waste treatment methods

**Disposal of wastes** Dispose of in accordance with federal, state and local regulations.

Contaminated packaging

Pressurized container: Do not pierce or burn, even after use. Do not puncture or incinerate container. If empty: Place in trash or offer for recycling if available. If partly filled: Call your local solid waste agency for disposal instructions.

Chemical name	RCRA	RCRA - Basis for Listing	<b>RCRA - D Series Wastes</b>	<b>RCRA - U Series Wastes</b>
Acetone		Included in waste stream:		U002
67-64-1		F039		

Chemical name	California Hazardous Waste Status
Acetone	Ignitable
67-64-1	

# 14. Transport Information

<u>DOT</u> UN/ID no Proper Shipping Name Hazard Class	Limited Quantity Consumer Commodity ORM-D
<u>IATA</u> UN/ID no Proper Shipping Name Hazard Class	UN1950 Aerosols, flammable 2.1
<u>IMDG</u> UN/ID no Proper Shipping Name	UN1950 Aerosols, flammable

2.1 This product does not contain marine pollutants.

## 15. Regulatory information

# International Inventories TSCA

Hazard Class

Marine pollutant

All ingredients of this product are listed or are excluded from listing under the U.S. Toxic Subtances Control Act (TSCA) Chemical Substance Inventory. All ingredients are listed or are excluded from listing on the DSL.

#### DSL Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

## US Federal Regulations

#### SARA 313

This product contains the following toxic chemicals (above the de minimis level) subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-to-Know Act of 1986 and 40 CFR 372. This information must be included in all SDSs that are copied and distributed for this material.

Chemical name	CAS No	weight-%	SARA 313 - Threshold Values %
Diethylene Glycol Monoethyl Ether - 111-90-0	111-90-0	20-25	1.0

## SARA 311/312 Hazard Categories

Acute Health Hazard	yes
Chronic Health Hazard	No
Fire Hazard	yes
Sudden release of pressure hazard	No
Reactive Hazard	No

#### CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

## **CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Acetone	5000 lb		RQ 5000 lb final RQ
67-64-1			RQ 2270 kg final RQ

## US State Regulations

### **California Proposition 65**

This product does not contain any Proposition 65 chemicals

## U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
Acetone 67-64-1	Х	X	Х
Diethylene Glycol Monoethyl Ether 111-90-0	Х		Х
N-Butane 106-97-8	Х	X	Х
1,1-Difluoroethane 75-37-6	Х	X	
Propane 74-98-6	Х	X	Х

#### U.S. EPA Label information

EPA Pesticide registration number Not applicable

16. Other information				
NFPA_	Health Hazards 2	Flammability 4	Instability 1	Physical and chemical properties Not applicable
<u>HMIS</u>	Health Hazards 2	Flammability 4	Physical hazards 1	Personal Protection B - Eyes and hands protection

Prepared by R Issue date 09

Regulatory Department 05-Mar-2019

**Revision note** 

This SDS supersedes a previous SDS dated December 16, 2014.

**Disclaimer** 

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

#### End of Safety Data Sheet