

X Close this window

SDS

Common Name: POW-R WRAP

Manufacturer: ACCESS-ABLE TECHNOLOGIES

SDS Revision Date: 9/14/2015

SDS Format: GHS-US

Item Number(s): 2KUT3, 2KUT4, 2KUT5

Manufacturer Model Number(s):

#### **SDS Table of Contents**

Click the desired link below to jump directly to that section in the SDS.

SECTION 1: CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

SECTION 2: HAZARDS IDENTIFICATION

SECTION 3: COMPOSITION, INFORMATION ON INGREDIENTS

SECTION 4: FIRST AID MEASURES

SECTION 5: FIRE-FIGHTING MEASURES

SECTION 6: ACCIDENTAL RELEASE MEASURES

SECTION 7: HANDLING AND STORAGE

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

SECTION 10: STABILITY AND REACTIVITY

SECTION 11: TOXICOLOGICAL INFORMATION

SECTION 12: ECOLOGICAL INFORMATION

SECTION 13: DISPOSAL CONSIDERATIONS

SECTION 14: TRANSPORT INFORMATION

SECTION 15: REGULATORY INFORMATION

SECTION 16: OTHER INFORMATION

ATI

ACCESS-ABLE TECHNOLOGIES, INC.

SAFETY DATA SHEET

THIS SDS COMPLIES WITH REACH 1907/2006 AND 2001/58/EC, GHS, OSHA 29CFR 1910.1200

### **SECTION 1: CHEMICAL PRODUCT AND COMPANY IDENTIFICATION**

🛆 top

CHEMICAL SUPPLIER COMPANY NAME: ACCESS-ABLE TECHNOLOGIES, INC. 1275 BENNETT DRIVE UNIT #115 LONGWOOD, FLORIDA 32750

EMERGENCY TELEPHONE:

CHEMTREC 24 HRS USA: 800-424-9300 CHEMTREC INTERNATIONAL: 703-527-3887

INFORMATION: 407-834-2999

FAX: 407-834-8992

SAFETY DATA SHEET COMPETENT PERSON: INFO@ACCESSABLETECH.COM

DATE PREPARED: APRIL 12, 2012

REVISION DATE: SEPTEMBER 14, 2015

PRODUCT NAME: POW-R WRAP

FORMULA: PREPARATION/MIXTURE

PRODUCT USE:

REPAIR OF LEAKS IN ALL TYPES OF PIPES, HOSES, AND LINES THAT MAY CONTAIN

FLUIDS, GASES, OR ANY OTHER TYPE OF MATERIAL.

### **SECTION 2: HAZARDS IDENTIFICATION**

🛆 top

EXCLAMATION MARK HEALTH HAZARD

GHS HAZARD CLASS:

ACUTE TOXICITY INHALATION: CATEGORY 4
SENSITIZATION RESPIRATORY: CATEGORY 1

SENSITIZATION SKIN: CATEGORY 1

SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE: CATEGORY 3
SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE: CATEGORY 2

SIGNAL WORD: DANGER

HAZARD STATEMENT:

H332: HARMFUL IF INHALED

н334:

MAY CAUSE ALLERGY OR ASTHMA SYMPTOMS OR BREATHING DIFFICULTIES IF INHALED.

H317: MAY CAUSE ALLERGIC SKIN REACTION.

H335: MAY CAUSE RESPIRATORY IRRITATION;

H373: MAY CAUSE DAMAGE TO ORGANS THROUGH PROLONGED OR REPEATED EXPOSURE.

PRECAUTIONARY STATEMENTS:

PREVENTION:

P261: AVOID BREATHING DUST/FUME/GAS/MIST/VAPOURS/SPRAY

P271: USE ONLY OUTDOORS OR IN A WELL-VENTILATED AREA.

P284: IN CASE OF INADEQUATE VENTILATION WEAR RESPIRATORY PROTECTION.

P272:

CONTAMINATED WORK CLOTHING SHOULD NOT BE ALLOWED OUT OF THE WORKPLACE.

P280:

WEAR PROTECTIVE GLOVES/PROTECTIVE CLOTHING/EYE PROTECTION/FACE PROTECTION.

**RESPONSE:** 

P304 + P340:

IF INHALED:

REMOVE VICTIM TO FRESH AIR AND KEEP AT REST IN A POSITION COMFORTABLE FOR BREATHING.

P312: CALL A POISON CENTER OR DOCTOR/PHYSICIAN IF YOU FEEL UNWELL.

P342 + P311:

IF EXPERIENCING RESPIRATORY SYMPTOMS: CALL A POISON CENTER OR DOCTOR.

P302 + P352:

IF ON SKIN: WASH WITH PLENTY OF WATER.

P333 + P313:

IF SKIN IRRITATION OR RASH OCCURS: GET MEDICAL ADVICE/ATTENTION.

P321: SPECIFIC TREATMENT (SEE SUPPLEMENTAL FIRST AID ON LABEL)

P362 + P364: TAKE OFF CONTAMINATED CLOTHING AND WASH IT BEFORE REUSE.

P314: GET MEDICAL ADVICE/ATTENTION IF YOU FEEL UNWELL.

STORAGE:

P403 + P233:

STORE IN A WELL VENTILATED PLACE. KEEP CONTAINER TIGHTLY CLOSED.

P405: STORE LOCKED UP.

DISPOSAL:

P501:

DISPOSE OF CONTENTS/CONTAINER:

FOLLOW THE WASTE DISPOSAL REQUIREMENTS OF YOUR COUNTRY, STATE, OR LOCAL AUTHORITIES.

<5% OF MIXTURE CONSISTS OF INGREDIENTS OF UNKNOWN ACUTE TOXICITY

HAZARD CLASSIFICATION: NOT CLASSIFIED AS HAZARDOUS BASED ON IMO AND DOT.

FIRE AND EXPLOSION:

NOT CONSIDERED FLAMMABLE OR COMBUSTIBLE, BUT THIS PRODUCT WILL BURN IF INVOLVED IN A FIRE. PRODUCT EMITS TOXIC FUMES WHEN BURNED.

APPEARANCE: FIBERGLASS TAPE IMPREGNATED WITH GREY LIQUID

NFPA RATING:

COMPONENT	HEALTH (BLUE)	FLAMMABILITY (RED)	REACTIVITY (YELLOW)	SPECIAL (WHITE)	
POW-R WRAP	2	0	0		

# **SECTION 3: COMPOSITION, INFORMATION ON INGREDIENTS**

PRODUCT COMPOSITION	APPROX %	CAS NO.	EC NUMBER	CANADA DSL
FIBERGLASS	40 - 60	65997-17-3		
4,4'-DIPHENYLMETHANE DIISOCYANATE (MDI)	10 20	101-68-8	202-966-0	Y
POLYISOCYANATE PREPOLYMER BASED ON MDI	30 - 50	TS	TS	TS
POLYMERIC DIPHENYLMETHANE DIISOCYANATE (PMDI)	<5	9016-87-9		Y
DIPHENYLMETHANE DIISOCYANATE (MDI) MIXED ISOMERS	<5	26447-40-5		Y
POLYESTER RESIN	<5	TS	TS	TS

TRADE SECRET (TS) SOME ITEMS ON THIS MSDS MAY BE DESIGNATED AS TRADE SECRETS. BONAFIDE REQUESTS FOR DISCLOSURE OF TRADE SECRET INFORMATION TO MEDICAL PERSONNEL MUST BE MADE IN ACCORDANCE WITH THE PROVISIONS CONTAINED IN 29 CFR 1910.1200 I 1-13. THE FULL TEXT FOR ALL R-PHRASES IS SHOWN IN SECTION 16.

### **SECTION 4: FIRST AID MEASURES**

🕰 top

7

DESCRIPTION OF FIRST AID MEASURES:

#### INHALATION:

REMOVE TO FRESH AIR. IF NOT BREATHING, PROVIDE CPR (CARDIO PULMONARY RESUSCITATION). GET IMMEDIATE MEDICAL ATTENTION.

#### SKIN CONTACT:

IMMEDIATELY WASH SKIN WITH PLENTY OF SOAP AND WATER FOR AT LEAST 15 MINUTES. REMOVE CONTAMINATED CLOTHING.

#### EYE CONTACT:

IMMEDIATELY FLUSH EYES WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES. GET IMMEDIATE MEDICAL ATTENTION.

#### INGESTION:

IF SWALLOWED DO NOT INDUCE VOMITING, GIVE LARGE QUANTITIES OF WATER TO DRINK. NEVER GIVE ANYTHING TO AN UNCONSCIOUS PERSON. GET IMMEDIATE MEDICAL ATTENTION.

MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED:

#### SYMPTOMS/INJURIES AFTER INHALATION:

MAY CAUSE RESPIRATORY TRACT IRRITATION. MAY CAUSE DIZZINESS, HEADACHE, NAUSEA AND MENTAL CONFUSION.

## SYMPTOMS/INJURIES AFTER SKIN CONTACT:

MAY CAUSE SKIN IRRITATION. SYMPTOMS MAY INCLUDE REDNESS, DRYING, DEFATTING, AND CRACKING OF THE SKIN.

### SYMPTOMS/INJURIES AFTER EYE CONTACT:

MAY CAUSE EYE IRRITATION. SYMPTOMS MAY INCLUDE DISCOMFORT OR PAIN, EXCESS BLINKING AND TEAR PRODUCTION, WITH POSSIBLE REDNESS AND SWELLING.

### SYMPTOMS/INJURIES AFTER INGESTION:

MAY BE HARMFUL IF SWALLOWED. MAY CAUSE STOMACH DISTRESS, NAUSEA, OR VOMITING.

INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED: SYMPTOMS MAY NOT APPEAR IMMEDIATELY. IN CASE OF ACCIDENT OR IF YOU FEEL UNWELL, SEEK MEDICAL ADVICE IMMEDIATELY.

### ACUTE:

DIISOCYANATE VAPORS OR MIST AT CONCENTRATIONS ABOVE THE TLV OR PEL CAN IRRITATE (BURNING SENSATION) THE MUCOUS MEMBRANES IN THE RESPIRATORY TRACT (NOSE, THROAT, LUNGS) CAUSING RUNNY NOSE, SORE THROAT, COUGHING, CHEST DISCOMFORT, SHORTNESS OF BREATH AND REDUCED LUNG FUNCTION (BREATHING OBSTRUCTION). PERSONS WITH A PREEXISTING, NONSPECIFIC BRONCHIAL HYPERREACTIVITY CAN RESPOND TO CONCENTRATIONS BELOW THE TLV OR PEL WITH SIMILAR SYMPTOMS AS WELL AS ASTHMA ATTACK OR ASTHMA-LIKE SYMPTOMS. EXPOSURE WELL ABOVE THE TLV OR PEL MAY LEAD TO BRONCHITIS, BRONCHIAL SPASM AND PULMONARY EDEMA (FLUID IN LUNGS). CHEMICAL OR HYPERSENSITIVITY PNEUMONITIS, WITH FLU-LIKE SYMPTOMS (E.G., FEVER, CHILLS), HAS ALSO BEEN REPORTED. THESE SYMPTOMS CAN BE DELAYED UP TO SEVERAL HOURS AFTER EXPOSURE. THESE EFFECTS ARE USUALLY REVERSIBLE.

CAUSES SKIN IRRITATION WITH SYMPTOMS OF REDDENING, ITCHING, AND SWELLING. PERSONS PREVIOUSLY SENSITIZED CAN EXPERIENCE ALLERGIC SKIN REACTION WITH

SYMPTOMS OF REDDENING, ITCHING, SWELLING, AND RASH. CURED MATERIAL IS DIFFICULT TO REMOVE. CONTACT WITH MDI CAN CAUSE DISCOLORATION.

CAUSES EYE IRRITATION WITH SYMPTOMS OF REDDENING, TEARING, STINGING, AND SWELLING. MAY CAUSE TEMPORARY CORNEAL INJURY. VAPOR OR AEROSOL MAY CAUSE IRRITATION WITH SYMPTOMS OF BURNING AND TEARING.

MAY CAUSE IRRITATION OF THE DIGESTIVE TRACT. SYMPTOMS MAY INCLUDE ABDOMINAL PAIN, NAUSEA, VOMITING, AND DIARRHEA.

#### CHRONIC:

AS A RESULT OF PREVIOUS REPEATED OVEREXPOSURES OR A SINGLE LARGE DOSE, CERTAIN INDIVIDUALS MAY DEVELOP SENSITIZATION TO ISOCYANATES (ASTHMA OR ASTHMA-LIKE SYMPTOMS) THAT MAY CAUSE THEM TO REACT TO A LATER EXPOSURE TO ISOCYANATES AT LEVELS WELL BELOW THE TLV OR PEL. THESE SYMPTOMS, WHICH CAN INCLUDE CHEST TIGHTNESS, WHEEZING, COUGH, SHORTNESS OF BREATH OR ASTHMATIC ATTACK, COULD BE IMMEDIATE OR DELAYED UP TO SEVERAL HOURS AFTER EXPOSURE. EXTREME ASTHMATIC REACTIONS CAN BE LIFE THREATENING. SIMILAR TO MANY NON-SPECIFIC ASTHMATIC RESPONSES, THERE ARE REPORTS THAT ONCE SENSITIZED AN INDIVIDUAL CAN EXPERIENCE THESE SYMPTOMS UPON EXPOSURE TO DUST, COLD AIR OR OTHER IRRITANTS. THIS INCREASED LUNG SENSITIVITY CAN PERSIST FOR WEEKS AND IN SEVERE CASES FOR SEVERAL YEARS. SENSITIZATION CAN BE PERMANENT. CHRONIC OVEREXPOSURE TO ISOCYANATES HAS ALSO BEEN REPORTED TO CAUSE LUNG DAMAGE (INCLUDING FIBROSIS, DECREASE IN LUNG FUNCTION) THAT MAY BE PERMANENT.

PROLONGED CONTACT WITH SKIN CAN CAUSE REDDENING, SWELLING, RASH, AND, IN SOME CASES, SKIN SENSITIZATION. ANIMAL TESTS AND OTHER RESEARCH INDICATE THAT SKIN CONTACT WITH MDI CAN PLAY A ROLE IN CAUSING ISOCYANATE SENSITIZATION AND RESPIRATORY REACTION. THIS DATA REINFORCES THE NEED TO PREVENT DIRECT SKIN CONTACT WITH ISOCYANATES.

## **SECTION 5: FIRE-FIGHTING MEASURES**

🛆 top

SUITABLE EXTINGUISHING MEDIA: USE FOAM, DRY CHEMICAL, OR CARBON DIOXIDE.

SPECIAL HAZARDS ARISING FROM THE SUBSTANCE OR MIXTURE: NO DATA AVAILABLE.

PROTECTIVE ACTIONS FIRE-FIGHTERS:

WEAR STANDARD PROTECTIVE EQUIPMENT AND SELF CONTAINED BREATHING APPARATUS FOR FIREFIGHTING IF NECESSARY.

FURTHER INFORMATION:

USE WATER SPRAY TO COOL UNOPENED CONTAINERS. EMITS TOXIC FUMES UNDER FIRE CONDITIONS.

## **SECTION 6: ACCIDENTAL RELEASE MEASURES**

A top

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT, AND EMERGENCY PROCEDURES: WEAR PROPER PERSONAL PROTECTIVE EQUIPMENT. AVOID BREATHING VAPORS OR MIST.

ENVIRONMENTAL PRECAUTIONS: NONE

METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING UP: PLACE WASTE MATERIAL OR UNUSED MATERIAL IN A WASTE CONTAINER.

REFERENCE TO OTHER SECTIONS:

FOR PERSONAL PROTECTION REFERENCE SECTION 8. FOR DISPOSAL REFERENCE SECTION 13.

### **SECTION 7: HANDLING AND STORAGE**

7

PRECAUTIONS FOR SAFE HANDLING:

USE ONLY WITH ADEQUATE VENTILATION.

DO NOT INHALE VAPORS.

WEAR PROPER PROTECTIVE EQUIPMENT WHEN HANDLING THIS MATERIAL.

AVOID CONTACT WITH SKIN, EYES OR CLOTHING.

WASH HANDS AND FACE AFTER HANDLING THIS MATERIAL.

KEEP OUT OF REACH OF CHILDREN.

CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES:

STORE UPRIGHT IN A COOL, DRY PLACE.

KEEP CONTAINER CLOSED WHEN NOT IN USE.

UTILIZE CHEMICAL SEGREGATION.

FOLLOW ALL APPLICABLE LOCAL REGULATIONS FOR HANDLING AND STORAGE.

#### SPECIFIC USES:

REPAIR OF LEAKS IN ALL TYPES OF PIPES, HOSES, AND LINES THAT MAY CONTAIN FLUIDS, GASES, OR ANY OTHER TYPE OF MATERIAL.

## **SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

🛆 top

CONTROL PARAMETERS:

PRODUCT COMPOSITION

ACGIH TLV

TLV OSHA PEL

NIOSH REL

101-68-8

0.005 PPM

0.02 PPM;

0.2 MG/M3

### EXPOSURE CONTROLS:

### **VENTILATION:**

ALWAYS PROVIDE GOOD GENERAL, MECHANICAL ROOM VENTILATION WHERE THIS CHEMICAL/MATERIAL IS USED.

### RESPIRATORY PROTECTION:

USE A SUITABLE RESPIRATORY PROTECTIVE DEVICE IN CASE OF INSUFFICIENT VENTILATION. FOLLOW THE OSHA RESPIRATOR REGULATIONS FOUND IN 29 CFR 1910.134 OR THE EUROPEAN STANDARD EN 149. USE A NIOSH/MSHA OR EUROPEAN STANDARD EN 149 APPROVED RESPIRATOR IF EXPOSURE LIMITS ARE EXCEEDED OR IF IRRITATION OR OTHER SYMPTOMS ARE EXPERIENCED.

### PROTECTIVE GLOVES:

WEAR CHEMICAL IMPERVIOUS GLOVES AT ALL TIMES WHILE WORKING WITH THIS PRODUCT.

### RECOMMENDED GLOVE TYPES INCLUDE:

LAMINATE FILM, NITRILE, OR TRI-POLYMER. CHECK WITH YOUR COMPANY'S GLOVE SUPPLIER TO ENSURE CHEMICAL RESISTANCE.

EYE PROTECTION: SAFETY GLASSES, CHEMICAL GOGGLES, OR FACE SHIELD

#### PROTECTIVE CLOTHING:

WEAR SUITABLE PROTECTIVE CLOTHING TO PREVENT SKIN CONTACT.

### OTHER EQUIPMENT:

MAKE SAFETY SHOWER, EYEWASH STATIONS, AND HAND WASHING EQUIPMENT AVAILABLE IN THE WORK AREA.

### WORK/HYGIENE PRACTICES:

AVOID BREATHING VAPOR. AVOID CONTACT WITH EYES. WASH HANDS AND FACE AFTER HANDLING.

### **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

PRODUCT CRITERIA:

APPEARANCE - COLOR: GREY

PHYSICAL STATE: FIBERGLASS TAPE IMPREGNATED WITH GREY LIQUID

ODOR: SLIGHT AROMATIC ODOR

ODOR THRESHOLD: NO DATA AVAILABLE

PH: NO DATA AVAILABLE

MELTING POINT/FREEZING POINT: NO DATA AVAILABLE

INITIAL BOILING POINT AND BOILING RANGE:

APPROX. 694 DEG. F (367.78) DEG. C ESTIMATED BASED UPON COMPONENTS

FLASH POINT: 460 DEG. F (237.78 DEG. C) PENSKY-MARTENS CLOSED CUP ASTM D-93

EVAPORATION RATE: NO DATA AVAILABLE

FLAMMABILITY (SOLID, GAS): NO DATA AVAILABLE

UPPER/LOWER FLAMMABILITY OR EXPLOSIVE LIMITS: NOT MEASURED

VAPOR PRESSURE: <0.0001 MMHg @ 77 DEG. F (25 DEG. C)

VAPOR DENSITY (AIR = 1): APPROX. 1.14 G/CM3 @ 77 DEG. F (25 DEG. C)

RELATIVE DENSITY (@25 DEG. C): 1.14

SOLUBILITY (IES):

INSOLUBLE - REACTS SLOWLY WITH WATER TO LIBERATE CO2 GAS

OXIDIZING PROPERTIES: NO DATA AVAILABLE

PARTITION COEFFICIENT N-OCTANOL/WATER: NO DATA AVAILABLE

AUTO IGNITION TEMPERATURE: NO DATA AVAILABLE

DECOMPOSITION TEMPERATURE: NO DATA AVAILABLE

VISCOSITY: APPROXIMATELY 5400 MPAS @ 77 DEG. F (25 DEG. C)

VOC CONTENT: NO DATA AVAILABLE

## **SECTION 10: STABILITY AND REACTIVITY**

🛆 top

REACTIVITY: WATER REACTS WITH THE CHEMICALS IN THE TAPE.

CHEMICAL STABILITY: STABLE

POSSIBILITY OF HAZARDOUS REACTIONS: WILL NOT OCCUR

CONDITIONS TO AVOID: NONE

INCOMPATIBILITY (MATERIALS TO AVOID): WATER

HAZARDOUS DECOMPOSITION PRODUCTS: NONE

## **SECTION 11: TOXICOLOGICAL INFORMATION**

GHS REQUIRED CRITERIA	TOXICITY CRITERIA			CHEMICAL CONSTITUENT
ACUTE TOXICITY	LD50 (ORAL/RAT)	>2000 MG/KG		9016-87-9 PMDI
	LC50 (INHALATION/ RAT MALE)	0.49 MG/L / 4 HOUR		9016-87-9 PMDI
	LD50 (DERMAL/RABBIT)	>9400 MG/KG		9016-87-9 PMDI
	LC50 (INHALATION/ RAT MALE)	0.369 MG/L / 4 HOUR		101-68-8
	LD50 (ORAL/RAT)	>7616 MG/KG		101-68-8
	LD50 (DERMAL/RABBIT)	>9400 MG/KG		101-68-8
SKIN CORROSION/ IRRITATION		NO INFORMATION IS AVAILABLE.		
SERIOUS EYE DAMAGE / EYE IRRITATION		NO INFORMATION IS AVAILABLE.		
RESPIRATORY OR SKIN SENSITIZATION	SKIN SENSITIZATION (LOCAL LYMPH NODE ASSAY (LLNA)): POSITIVE (MOUSE, OECD EST GUIDELINE 429)			101-68-8
	RESPIRATORY SENSIT		101-68-8	
	SKIN SENSITIZATION BUEHLER (EPICUTANE NEGATIVE (GUINEA E TEST GUIDELINE 406		9016-87-9 PMDI	
GERM CELL MUTAGENICITY	GENETIC TOXICITY I MICRO NUCLEUS ASSA (MOUSE) NEGATIVE		101-68-8	
	GENETIC TOXICITY I BACTERIAL - GENE M NEGATIVE (SALMONEI METABOLIC ACTIVATI WITH/WITHOUT)		9016-87-9 PMDI	
CARCINOGENICITY	NTP	NOT LISTED		101-68-8
	IARC	NOT CLASSIFIABLE AS TO ITS CARCINOGENICITY IN HUMANS (GROUP 3)		
	IARC	NOT CLASSIFIABLE AS TO ITS CARCINOGENICITY IN HUMANS (GROUP 3)		9016-87-9
	OSHA	NOT LISTED		

2/19/2019

Grainger SDS Lookup

REPRODUCTIVE TOXICITY

NO INFORMATION IS AVAILABLE.

STOT - SINGLE

MAY CAUSE RESPIRATORY IRRITATION

EXPOSURE

CAT 3

9016-87-9

9016-87-9

EXPOSURE

STOT - REPEATED MAY CAUSE DAMAGE TO ORGANS THROUGH CAT 2

PROLONGED OR REPEATED EXPOSURE-

INHALATION

ASPIRATION

NO INFORMATION IS AVAILABLE.

HAZARD AMES TEST

NEGATIVE

9016-87-9

NEGATIVE

101-68-8

STOT = SPECIFIC TARGET ORGAN TOXICITY

### **SECTION 12: ECOLOGICAL INFORMATION**

🛆 top

CHEMICAL CONSTITUENT:

TOXICITY

EC50: >100 MG/L, (ACTIVATED SLUDGE, 3 H)

101-68-8

PERSISTENCE AND

DEGRADABILITY

NO INFORMATION IS AVAILABLE.

101-68-8

BIOACCUMULATIVE

ONCORHYNCHUS MYKISS (RAINBOW TROUT),

EXPOSURE TIME: 112 D, <1 BCF

MOBILITY IN SOIL NO INFORMATION IS AVAILABLE.

PB AND VPVB ASSESSMENT

POTENTIAL

PBT/VPVB ASSESSMENT NOT AVAILABLE AS CHEMICAL ASSESSMENT NOT REQUIRED/NOT

CONDUCTED

OTHER ADVERSE

NO INFORMATION IS AVAILABLE.

EFFECTS

# **SECTION 13: DISPOSAL CONSIDERATIONS**

🛆 top

WASTE FROM RESIDUES/UNUSED PRODUCTS:

FOLLOW THE WASTE DISPOSAL REQUIREMENTS OF YOUR COUNTRY, STATE, OR LOCAL AUTHORITIES.

CONTAMINATED PACKAGING:

CONTAMINATED PACKAGING MATERIAL SHOULD BE DISPOSED OF AS STATED ABOVE FOR RESIDUES AND UNUSED PRODUCT.

RINSATE:

DO NOT DISPOSE OF RINSE WATER CONTAINING PRODUCT IN A SANITARY SEWER SYSTEM OR STORMWATER DRAINAGE SYSTEM.

# **SECTION 14: TRANSPORT INFORMATION**

🛆 top

DOT TRANSPORT: NOT REGULATED

ADR = INTERNATIONAL CARRIAGE OF DANGEROUS GOODS BY ROAD: NOT REGULATED

RAIL TRANSPORT: NOT REGULATED

SEA TRANSPORT: IMDG NOT REGULATED

AIR TRANSPORT: IATA/ICAO NOT REGULATED

### **SECTION 15: REGULATORY INFORMATION**

 $\Delta$  top

TOXIC SUBSTANCES CONTROL ACT (TSCA) STATUS:

THIS PRODUCT IS IN COMPLIANCE WITH RULES, REGULATIONS, AND ORDERS OF TSCA. ALL COMPONENTS ARE EITHER LISTED ON THE TSCA INVENTORY OR ARE CONSIDERED EXEMPT.

SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1986 (SARA) TITLE III SECTION 313 SUPPLIER NOTIFICATION:

THIS REGULATION REQUIRES SUBMISSION OF ANNUAL REPORTS OF TOXIC CHEMICAL(S) THAT APPEAR IN SECTION 313 OF THE EMERGENCY PLANNING AND COMMUNITY RIGHT TO KNOW ACT OF 1986 AND 40 CFR 372. THIS INFORMATION MUST BE INCLUDED IN ALL MSDS'S THAT ARE COPIED AND DISTRIBUTED FOR THE MATERIAL.

THE SECTION 313 TOXIC CHEMICALS CONTAINED IN THIS PRODUCT ARE: ZINC SULFIDE CAS 1314-98-3

CALIFORNIA PROPOSITION 65:

THIS REGULATION REQUIRES A WARNING FOR CALIFORNIA PROPOSITION 65 CHEMICAL(S) UNDER THE STATUTE.

THE CALIFORNIA PROPOSITION 65 CHEMICAL(S) CONTAINED IN THIS PRODUCT ARE: NONE

STATE RIGHT-TO-KNOW TOXIC SUBSTANCE OR HAZARDOUS SUBSTANCE LIST:

FLORIDA TOXIC SUBSTANCE(S): NOT LISTED

MASSACHUSETTS'S HAZARDOUS SUBSTANCE(S): NOT LISTED

PENNSYLVANIA HAZARDOUS SUBSTANCE CODE(S): NOT LISTED

NEW JERSEY: NOT LISTED

ILLINOIS: NOT LISTED

MICHIGAN: NOT LISTED

CANADA:

WHMIS-2015: THIS SDS IS IN COMPLIANCE WITH WHMIS 2015 (HPR / NEW HPA).

EUROPEAN UNION:

THIS PRODUCT HAS BEEN REVIEWED FOR COMPLIANCE WITH THE FOLLOWING EUROPEAN COMMUNITY DIRECTIVES:

REACH 1907/2006; DIRECTIVE 67/548/EEC, REGULATION (EC) NO 1272/2008 ON CLASSIFICATION, LABELING, AND PACKAGING (CLP) OF SUBSTANCES AND MIXTURES.

# **SECTION 16: OTHER INFORMATION**

🛆 top

INITIAL ISSUE DATE: AUGUST 8, 2015

FINAL REVISION DATE: SEPTEMBER 14, 2015

REVISION NUMBER: 0

REVISION EXPLANATION: INITIAL VERSION

INFORMATION SOURCES: RTECS, ECHA, REACH, OSHA 29CFR 1910.1200

#### "DISCLAIMER:

THIS DOCUMENT IS GENERATED TO DISTRIBUTE HEALTH, SAFETY AND ENVIRONMENTAL DATA. IT IS NOT A SPECIFICATION SHEET AND NONE OF THE DISPLAYED DATA SHOULD BE CONSTRUED AS A SPECIFICATION. INFORMATION ON THIS SDS SHEET WAS OBTAINED FROM SOURCES WHICH WE BELIEVE ARE RELIABLE, AND WE BELIEVE THAT THE INFORMATION IS COMPLETE AND ACCURATE. HOWEVER, THE INFORMATION IS PROVIDED WITHOUT ANY WARRANTY, EXPRESS OR IMPLIED, REGARDING ITS CORRECTNESS. SOME OF THE INFORMATION PRESENTED AND CONCLUSIONS DRAWN ARE FROM SOURCES OTHER THAN DIRECT TEST DATA OF THE SUBSTANCE. THE CONDITIONS OR METHODS OF HANDLING, STORAGE, USE AND DISPOSAL OF THE PRODUCT ARE BEYOND OUR CONTROL AND MAY ALSO BE BEYOND OUR KNOWLEDGE. IT IS THE USER'S RESPONSIBILITY TO DETERMINE THE SUITABILITY OF ANY MATERIAL FOR A SPECIFIC PURPOSE AND TO ADOPT SUCH SAFETY PRECAUTIONS AS MAY BE NECESSARY. IF THE PRODUCT IS USED AS A COMPONENT IN ANOTHER PRODUCT, THIS SDS INFORMATION MAY NOT BE APPLICABLE. FOR THESE REASONS, WE DO NOT ASSUME ANY RESPONSIBILITY AND EXPRESSLY DISCLAIM LIABILITY FOR ANY LOSS, DAMAGE OR EXPENSE ARISING OUT OF OR IN ANY WAY CONNECTED WITH THE HANDLING, STORAGE, USE OR DISPOSAL OF THIS PRODUCT."

SDS AUTHORED BY: AEGIS

ENVIRONMENTAL STRATEGIES

WWW.AEGIS-EHS.COM

PART NO.: POW-R WRAP

				5
				• •
				•
			·	
		·		
	,			