

## SAFETY DATA SHEET

Revision date 09-Jan-2018

Version 24

Supersedes Date: 20-Oct-2017

# Section 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Product identifier

**Product Code** 

024.0000136

**Product Name** 

LTX ZONE MARK YLO

Other means of identification

No information available

Recommended use of the chemical and restrictions on use

Paint, Coatings

Details of the supplier of the safety data sheet

See section 16 for more information

The Valspar Corporation PO Box 1461

Minneapolis, MN 55440

E-mail address msds@valspar.com

Emergency telephone number

United States of America 1-888-345-5732

## **Section 2: HAZARDS IDENTIFICATION**

## Classification

Carcinogenicity	Category 1A
Specific target organ toxicity (repeated exposure)	Category 1

#### Label elements



#### Signal word

#### **DANGER**

#### **HAZARD STATEMENTS**

May cause cancer

Causes damage to organs through prolonged or repeated exposure

#### **PREVENTION**

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection. Do not breathe dust/fume/gas/mist/vapors/spray. Wash face, hands and any exposed skin thoroughly after handling. Do not eat, drink or smoke when using this product.

#### **RESPONSE**

IF exposed or concerned: Get medical advice/attention.

#### **Eyes**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

#### Skin

Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention.

#### Inhalation

IF INHALED: Call a POISON CENTER or doctor if you feel unwell.

#### Ingestion

Do NOT induce vomiting. IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.

## **STORAGE**

Store locked up.

#### **DISPOSAL**

Dispose of contents/containers in accordance with local regulations.

## HAZARDS NOT OTHERWISE CLASSIFIED (HNOC)

No information available.

## **OTHER HAZARDS**

Not applicable.

#### **UNKNOWN ACUTE TOXICITY**

.0001% of the mixture consists of ingredient(s) of unknown toxicity.

## **Section 3: COMPOSITION/INFORMATION ON INGREDIENTS**

Chemical Name	CAS No	weight-%
Quartz	14808-60-7	5 - 10
Titanium dioxide	13463-67-7	3 - 5
Ethylene glycol	107-21-1	1 - 3

<sup>\*</sup>The exact percentage (concentration) of composition has been withheld as a trade secret.

## **Section 4: FIRST AID MEASURES**

## **First Aid Measures**

#### **General advice**

IF exposed or concerned: Get medical advice/attention.

#### Eye contact

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

#### Skin Contact

Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention.

#### Inhalation

IF INHALED: Call a POISON CENTER or doctor if you feel unwell.

#### Ingestion

Do NOT induce vomiting. IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.

## Most important symptoms and effects, both acute and delayed

**Symptoms** No information available.

#### Indication of any immediate medical attention and special treatment needed

**Note to physicians** Treat symptomatically.

## Section 5: FIRE FIGHTING MEASURES

#### Suitable extinguishing media

Dry chemical, CO2, water spray or alcohol-resistant foam.

Not to be used for safety reasons: Strong water jet

#### Specific hazards arising from the chemical

Burning produces heavy smoke. Fire may produce irritating and/or toxic gases. In the event of fire and/or explosion do not breathe fumes.

### Special protective equipment for fire-fighters

Wear self-contained breathing apparatus and protective suit. Cool containers with flooding quantities of water until well after fire is out. Do not allow run-off from fire-fighting to enter drains or water courses.

## Section 6: ACCIDENTAL RELEASE MEASURES

## Personal precautions, protective equipment and emergency procedures

#### **Personal precautions**

Avoid breathing vapors or mists. Remove all sources of ignition. Use personal protective equipment as required. Keep people away from and upwind of spill/leak. Avoid contact with skin, eyes or clothing.

### For emergency responders

Use personal protection recommended in Section 8.

## **Environmental precautions**

Do not allow into any sewer, on the ground or into any body of water. If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations.

#### Methods and material for containment and cleaning up

## **Methods for containment**

Prevent further leakage or spillage if safe to do so.

## Methods for cleaning up

Dispose of waste product or used containers according to local regulations. Clean with detergents. Avoid solvent cleaners. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Pick up and transfer to properly labeled containers.

## **Section 7: HANDLING AND STORAGE**

#### Precautions for safe handling

#### Advice on safe handling

Prevent the creation of flammable or explosive concentrations of vapor in air and avoid vapor concentration higher than the occupational exposure limits. Use personal protection recommended in Section 8. Never use pressure to empty container. Comply with the health and safety at work laws. Prevent product from entering drains. Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air. Do not breathe dust/fume/gas/mist/vapors/spray.

#### **General Hygiene Considerations**

Avoid contact with skin, eyes or clothing. When using do not eat, drink or smoke. Wash contaminated clothing before reuse.

#### Conditions for safe storage, including any incompatibilities

#### **Storage Conditions**

Keep/store only in original container. Store in accordance with local regulations. Keep unauthorized personnel away. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

## Incompatible materials

Strong oxidizing agents. Acids.

## Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Control parameters

## **Exposure Limits**

If S\* appears in the OEL table, it indicates this chemical contains a skin notation.

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Quartz	TWA: 0.025 mg/m³ respirable	TWA: 50 μg/m <sup>3</sup>	IDLH: 50 mg/m <sup>3</sup> respirable dust
14808-60-7	particulate matter	TWA: (250)/(%SiO2 + 5) mppcf	TWA: 0.05 mg/m³ respirable dust
		TWA respirable fraction	
		TWA: (10)/(%SiO2 + 2) mg/m <sup>3</sup>	
		TWA respirable fraction	
Titanium dioxide	TWA: 10 mg/m <sup>3</sup>	TWA: 15 mg/m <sup>3</sup> total dust	IDLH: 5000 mg/m <sup>3</sup>
13463-67-7			
Ethylene glycol	Ceiling: 100 mg/m <sup>3</sup> aerosol only		
107-21-1			

## **Appropriate engineering controls**

#### **Engineering Controls**

Ensure adequate ventilation, especially in confined areas. Provide local exhaust ventilation. In case of insufficient ventilation, wear suitable respiratory equipment.

## Individual protection measures, such as personal protective equipment

#### Eye/face protection

Wear safety glasses with side shields (or goggles).

#### Skin and body protection

Wear suitable protective clothing.

## **Hand Protection**

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed. Gloves should be replaced regularly and if there is any sign of damage to the glove material. Always ensure that gloves are free from defects and that they are stored and used correctly. The performance or effectiveness of the glove may be reduced by physical / chemical damage and poor maintenance. Wear protective gloves.

## Respiratory protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

## **Section 9: PHYSICAL AND CHEMICAL PROPERTIES**

## Information on basic physical and chemical properties

Physical state liquid

Appearance No information available

Odor Slight Color yellow

Odor ThresholdNo information availablepH valueNo information availableMelting point/freezing pointNo information available

Boiling point / boiling range No information available °C / °F

flash point 96 °C / 205 °F

evaporation rate No information available Flammability (solid, gas) No information available

Flammability Limit in Air

Upper flammability limit:
Lower flammability limit:
Vapor Pressure
vapor density

No information available
No information available
No information available

Density (lbs per US gallon) 11.83

specific gravity
Solubility(ies)
Partition coefficient
Autoignition temperature
Decomposition temperature
Kinematic viscosity
No information available

**Other information** 

## Section 10: STABILITY AND REACTIVITY

**Reactivity** No information available.

Chemical stability Stable under normal conditions.

Possibility of Hazardous Reactions None under normal processing.

**Hazardous polymerization**None under normal processing.

**Conditions to avoid** Heat, flames and sparks.

**Incompatible materials** Strong oxidizing agents. Acids.

Hazardous Decomposition Products Carbon monoxide. Carbon dioxide (CO2).

## Section 11: TOXICOLOGICAL INFORMATION

## Information on likely routes of exposure

Eye contact Not applicable Skin Contact Not applicable Ingestion Not applicable

Inhalation Not applicable

## Numerical measures of toxicity - Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Quartz	= 500 mg/kg (Rat)	-	-
14808-60-7			
Titanium dioxide	> 10000 mg/kg (Rat)	-	-
13463-67-7			
Ethylene glycol	= 4700 mg/kg (Rat)	= 10600 mg/kg (Rat) = 9530 μL/kg	-
107-21-1		( Rabbit )	

## Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 23492 Mg/kg

**UNKNOWN ACUTE TOXICITY** .0001% of the mixture consists of ingredient(s) of unknown toxicity.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

## Carcinogenicity

According to IARC, Volume 93, no significant exposure to primary particles of titanium dioxide is thought to occur from use in paints since the pigment is bound to other materials.

Chemical Name	ACGIH	IARC	NTP	OSHA
Quartz 14808-60-7	A2	Group 1	Known	X
Titanium dioxide 13463-67-7		Group 2B		X

ACGIH (American Conference of Governmental Industrial Hygienists)

A2 - Suspected Human Carcinogen.

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans. Group 2B - Possibly Carcinogenic to Humans.

NTP (National Toxicology Program)

Known - Known Carcinogen.

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present.

Skin corrosion/irritation Not applicable

Serious eye damage/eye irritation Not applicable

Skin sensitization Not applicable

Respiratory sensitization Not applicable

Germ cell mutagenicity Not applicable

Carcinogenicity May cause cancer

Reproductive Toxicity Not applicable

Specific target organ toxicity (single exposure) Not applicable

Specific target organ toxicity (repeated exposure) Causes damage to organs through prolonged or repeated exposure

Aspiration hazard Not applicable

## Section 12: ECOLOGICAL INFORMATION

**Ecotoxicity** 

Environmental precautions Prevent product from entering drains.

Persistence and degradability

No information available

**Bioaccumulation** 

No information available

**Mobility** 

No information available

Other adverse effects No information available

## Section 13: DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes Disposal should be in accordance with applicable regional, national and local laws and

regulations.

Contaminated packaging Improper disposal or reuse of this container may be dangerous and illegal. Empty

containers must be scrapped or reconditioned.

## **Section 14: TRANSPORT INFORMATION**

DOT IMDG IATA

14.1 UN/ID no Not regulated Not regulated Not regulated

14.2 Proper shipping name

14.3 Hazard Class

14.4 Packing Group

14.5 Environmental hazard Not applicable

14.6 Special Provisions

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

No information available

The supplier may apply one of the following exceptions: Combustible Liquid (49 CFR 173.150(f)); Consumer Commodity (49 CFR 173.150(c), ICAO/IATA SP A112); Limited Quantity (49 CFR 173.150(b), ICAO Part 3 Chapter 4, IATA 2.7, IMDG Chapter 3.4); Viscous Liquid (49 CFR 173.121(b), IMDG 2.3.2.2, IATA 3.3.3.1.1, ICAO 3.2.2, ADR 2.2.3.1.5); Does Not Sustain Combustion (49 CFR 173.120(a), IATA 3.3.1.3, ICAO 3.1.3, IMDG 2.3.1.3, ADR 2.2.3.1.1 Note 1); or others as allowed under hazardous materials/dangerous goods regulations.

## **Section 15: REGULATORY INFORMATION**

## **International Inventories**

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

All components are listed or exempt

from listing.

**DSL** - Canadian Domestic Substances List

All components are listed or exempt from listing

## **US Federal Regulations**

A component in this material is subject to the following SNUR under TSCA 5(a)(2):

79 FR 59186

A component in this material is subject to the following SNUR under TSCA 5(a)(2):

79 FR 59186

Chemical Name	SARA 313 - Threshold Values	Metals	Hazardous air pollutants
	%		(HAPs) content
Ethylene glycol	1		Present
107-21-1			
1 - 3			

## SARA 311/312 Hazard Categories

Acute health hazard Yes
Chronic Health Hazard Yes
Fire hazard No
Sudden release of pressure hazard No
Reactive Hazard No

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Ethylene glycol	5000 lb		RQ 5000 lb final RQ
107-21-1			RQ 2270 kg final RQ

## **US State Regulations**

## Rule 66 status of product

Not photochemically reactive.

#### **California Proposition 65**

WARNING! This product contains a chemical known in the State of California to cause cancer.

#### U.S. EPA Label information

EPA Pesticide registration number Not applicable

## **U.S. State Right-to-Know Regulations**

Chemical Name	
Water	
7732-18-5	
Limestone	
1317-65-3	
Proprietary Non-Hazardous Ingredient - Proprietary CAS	
Quartz	
14808-60-7	
Titanium dioxide	
13463-67-7	
Ethylene glycol	
107-21-1	

## **Section 16: OTHER INFORMATION**

HMIS

**Supplier Address** 

Valspar Consumer The Valspar Corporation Valspar Plasti-Kote Headquarters 4999 36th St. Valspar Plasti-Kote 1636 Shawson Dr.

8725 W. Higgins Rd. Suite Grand Rapids, MI 49512 Mississauga, Ontario L4W 1N7

1000 800-253-3957 905-671-8333

Chicago, IL 60631 773-628-5500

Prepared By Product Stewardship

Revision date 09-Jan-2018

Revision Note No information available

Disclaimer

The information on this Safety Data Sheet (SDS) is based on the present state of our knowledge, current national legislation and guidelines. As the specific conditions of use of the product are outside the supplier's knowledge and control the user is responsible for ensuring that the requirements of relevant legislation are complied with. This SDS should not be construed as any guarantee of the technical performance or suitability for particular applications. UNLESS SUPPLIER AGREES OTHERWISE IN WRITING, SUPPLIER MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. SUPPLIER WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.

**End of Safety Data Sheet**