

# SAFETY DATA SHEET

## Section 1: IDENTIFICATION

### 1.1 PRODUCT IDENTIFIER

**Product Name:** SKD-S2 Aerosol

**Product Code:** Not available.

### 1.2 RECOMMENDED USE OF CHEMICAL AND RESTRICTIONS ON USE

**Use:** Non-Destructive Testing.

### 1.3 DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEET

**Name/Address:** Magnaflux  
155 Harlem Avenue  
Glenview, Illinois  
60025

**Telephone Number:** 847-657-5300

### 1.4 EMERGENCY TELEPHONE NUMBER

**Emergency Telephone Number:** CHEMTREC 800-424-9300

**Date of Preparation:** November 25, 2013 **Version #:** 1.1

## Section 2: HAZARD(S) IDENTIFICATION

### 2.1 CLASSIFICATION OF THE CHEMICAL ACCORDING TO OSHA HAZCOM 2012

#### Hazard class

Flammable Aerosol 1  
Gases Under Pressure - Compressed Gas  
Eye irritation 2A  
Specific target organ toxicity - Single exposure 3  
Specific target organ toxicity - Repeated exposure 1

### 2.2 LABEL ELEMENTS ACCORDING TO OSHA HAZCOM 2012

#### Hazard Pictogram:



**Signal Word:** Danger

**Hazard Statement:** Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes serious eye irritation. May cause drowsiness or dizziness. Causes damage to lungs through prolonged or repeated exposure.

**Prevention:** Keep away from heat/sparks/open flames/hot surfaces. -No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Wash hands thoroughly after handling. Wear eye protection/face protection. Use only outdoors or in a well-ventilated area. Do not breathe dust/fume/gas/mist/vapors/spray. Do not eat, drink or smoke when using this product.

## SAFETY DATA SHEET

<b>Response:</b>	If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell.
<b>Storage:</b>	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Store in a well-ventilated place. Store locked up.
<b>Disposal:</b>	Dispose of contents and container in accordance with all local, regional, national and international regulations.


### 2.3 ADDITIONAL INFORMATION

**Hazards not otherwise classified:** Not applicable.

2 % of the mixture consists of ingredient(s) of unknown acute toxicity.

This product is a hazardous chemical as defined by NOM-018-STPS-2000.

**Mexico Classification:**



**Blue = Health   Red = Flammability   Yellow = Reactivity   White = Special**

**Hazard Rating:** 0 = minimal, 1 = slight, 2 = moderate, 3 = severe, 4 = extreme

**WHMIS Classification(s):**

- Class A - Compressed Gas
- Class B5 - Flammable Aerosol
- Class D2A - Chronic Toxic Effects
- Class D2B - Eye Irritant

**WHMIS Hazard Symbols:**



**WHMIS Signal Word:**

DANGER

### Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

#### 3.1 MIXTURES

Ingredient	UN #	H / F / R / *	CAS No	Wt. %
Isopropanol	UN1219	1/3/0	67-63-0	30 - 60
Petroleum gases, liquefied, sweetened	UN1075	Not available.	68476-86-8	15 - 40
Acetone	UN1090	1/3/0	67-64-1	10 - 30
Ceramic materials and wares, chemicals	Not available.	Not available.	66402-68-4	3 - 7
Talc	Not available.	Not available.	14807-96-6	1 - 5

## SAFETY DATA SHEET

Silica, crystalline, quartz	Not available.	Not available.	14808-60-7	< 0.1
-----------------------------	----------------	----------------	------------	-------

The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

\* Per NOM-018-STPS-2000

### Section 4: FIRST- AID MEASURES

#### 4.1 DESCRIPTION OF THE FIRST AID MEASURE

<b>Eye:</b>	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes, including under lids. If easy to do, remove contact lenses, if worn. Get medical attention immediately.
<b>Skin:</b>	In case of contact, immediately flush skin with plenty of water. Call a physician if irritation develops and persists.
<b>Inhalation:</b>	If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.
<b>Ingestion:</b>	If swallowed, do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get immediate medical advice/attention.

#### 4.2 MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED

<b>Eye:</b>	Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.
<b>Skin:</b>	May cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin.
<b>Inhalation:</b>	May cause respiratory tract irritation. May cause drowsiness or dizziness.
<b>Ingestion:</b>	May be harmful if swallowed. May cause stomach distress, nausea or vomiting.

#### 4.3 INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENTS NEEDED

<b>Note to Physicians:</b>	Symptoms may not appear immediately.
<b>Specific Treatments:</b>	In case of accident or if you feel unwell, seek medical advice immediately (show the label or SDS where possible).

### Section 5: FIRE-FIGHTING MEASURES

#### 5.1 FLAMMABILITY

<b>Flammability:</b>	Flammable by WHMIS/OSHA/NOM-018-STPS-2000 criteria.
----------------------	---

#### 5.2 EXTINGUISHING MEDIA

<b>Suitable Extinguishing Media:</b>	Water, foam, carbon dioxide.
<b>Unsuitable Extinguishing Media:</b>	Not available.

#### 5.3 SPECIAL HAZARDS ARISING FROM THE CHEMICAL

<b>Products of Combustion:</b>	May include, and are not limited to: oxides of carbon.
--------------------------------	--

#### Explosion Data:

**Sensitivity to Mechanical Impact:** Not available.

## SAFETY DATA SHEET

**Sensitivity to Static Discharge:** Not available.

### 5.4 SPECIAL PROTECTIVE EQUIPMENT AND PRECAUTIONS FOR FIRE FIGHTERS

Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA). Use water spray to keep fire-exposed containers cool. Containers may explode when heated.

### Section 6: ACCIDENTAL RELEASE MEASURES

#### 6.1 PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES

Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Eliminate sources of ignition.

#### 6.2 METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING - UP

**Methods for Containment:** Contain and/or absorb spill with inert material (e.g. sand, vermiculite), then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).

**Methods for Cleaning-Up:** Scoop up material and place in a disposal container. Provide ventilation.

### Section 7: HANDLING AND STORAGE

#### 7.1 PRECAUTIONS FOR SAFE HANDLING

**Handling:** Keep away from sources of ignition. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Container may explode if heated. Avoid contact with skin and eyes. Do not breathe dust/fume/gas/mist/vapors/spray. Do not swallow. Use only outdoors or in a well-ventilated area. When using do not eat, drink or smoke. Use non-sparking tools. (See section 8)

**General Hygiene Advice:** Launder contaminated clothing before reuse. Wash hands before eating, drinking, or smoking.

#### 7.2 CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES

**Storage:** Keep out of the reach of children. Store locked up. Protect from sunlight. Do not store at temperatures above 50 °C / 122 °F. Store in a well-ventilated place. (See section 10)

### Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1 CONTROL PARAMETERS

##### Exposure Guidelines

Occupational Exposure Limits		
Ingredient	OSHA-PEL	ACGIH-TLV
Isopropanol	400 ppm	200 ppm
Petroleum gases, liquefied, sweetened	1000 ppm	1000 ppm
Acetone	1000 ppm TWA; 2400 mg/m <sup>3</sup> TWA	500 ppm
Ceramic materials and wares, chemicals	5 mg/m <sup>3</sup>	Not available.
Talc	20 mppcf	2 mg/m <sup>3</sup> (resp)
Silica, crystalline, quartz	((10 mg/m <sup>3</sup> )/(%SiO <sub>2</sub> +2) TWA (resp)) ((30 mg/m <sup>3</sup> )/(%SiO <sub>2</sub> +2) TWA (total)) ((250)/(%SiO <sub>2</sub> +5) mppcf TWA (resp))	0.025 mg/m <sup>3</sup>

## SAFETY DATA SHEET

### 8.2 EXPOSURE CONTROLS

**Engineering Controls:** Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits.

### 8.3 INDIVIDUAL PROTECTIVE MEASURES

#### Personal Protective Equipment:

**Eye/Face Protection:** Safety glasses or goggles are recommended when using product.

#### Skin Protection:

**Hand Protection:** Chemical-resistant gloves.

**Body Protection:** Wear suitable protective clothing.

**Respiratory Protection:** In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

**General Health and Safety Measures:** Do not eat, smoke or drink where material is handled, processed or stored. Wash hands carefully before eating or smoking. Handle according to established industrial hygiene and safety practices.

## Section 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1 INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES

<b>Appearance:</b>	White liquid.
<b>Color:</b>	White.
<b>Odor:</b>	Alcohol.
<b>Odor Threshold:</b>	Not available.
<b>Physical State:</b>	Gas/Pressurized Liquid.
<b>pH:</b>	Neutral.
<b>Melting Point/Freezing Point:</b>	Not available.
<b>Initial Boiling Point and Boiling Range:</b>	~ 55 °C (~ 132 °F)
<b>Flash Point:</b>	Not applicable.
<b>Evaporation Rate:</b>	0.4 (Ether = 1)
<b>Flammability:</b>	Flammable.
<b>Lower Flammability/Explosive Limit:</b>	2 %
<b>Upper Flammability/Explosive Limit:</b>	15 %
<b>Vapor Pressure:</b>	65 psi @ 24 °C (75 °F)
<b>Vapor Density:</b>	3
<b>Relative Density/Specific Gravity:</b>	0.87
<b>Solubility:</b>	Partial.
<b>Partition coefficient: n-octanol/water:</b>	Not available.
<b>Auto-ignition Temperature:</b>	Not available.
<b>Decomposition Temperature:</b>	Not available.

## SAFETY DATA SHEET

**Viscosity:** Not available.

**Oxidizing Properties:** Not available.

**Explosive Properties:** Not available.

### Section 10: STABILITY AND REACTIVITY

#### 10.1 REACTIVITY

No dangerous reaction known under conditions of normal use.

#### 10.2 CHEMICAL STABILITY

Stable under normal storage conditions. Contents under pressure. Container may explode if heated. Do not pierce or burn, even after use.

#### 10.3 POSSIBILITY OF HAZARDOUS REACTIONS

No dangerous reaction known under conditions of normal use.

#### 10.4 CONDITIONS TO AVOID

Heat. Incompatible materials. Sources of ignition.

#### 10.5 INCOMPATIBLE MATERIALS

Strong oxidizing agents.

#### 10.6 HAZARDOUS DECOMPOSITION PRODUCTS

May include, and are not limited to: oxides of carbon.

### Section 11: TOXICOLOGICAL INFORMATION

#### 11.1 INFORMATION ON TOXICOLOGICAL EFFECTS

**Likely Routes of Exposure:** Skin contact, eye contact, inhalation, and ingestion.

**Symptoms related to physical/chemical/toxicological characteristics:**

**Eye:** Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.

**Skin:** May cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin.

**Ingestion:** May be harmful if swallowed. May cause stomach distress, nausea or vomiting.

**Inhalation:** May cause respiratory tract irritation. May cause drowsiness or dizziness.

**Acute Toxicity:**

Ingredient	IDLH	LC50	LD50
Isopropanol	2,000 ppm	Inhalation 72.6 mg/L 4h, rat	Oral 4396 mg/kg, rat Dermal 12800 mg/kg, rat Dermal 12870 mg/kg, rabbit
Petroleum gases, liquefied, sweetened	Not available.	Inhalation 658 mg/L 4h, rat	Not available.
Acetone	2,500 ppm	Inhalation 50100 mg/m <sup>3</sup> 8h, rat	Oral 5800 mg/kg, rat

## SAFETY DATA SHEET

Ceramic materials and wares, chemicals	Not available.	Not available.	Oral > 2000 mg/kg, rat Dermal > 2500 mg/kg, rabbit
Talc	1,000 mg/m <sup>3</sup>	Not available.	Not available.
Silica, crystalline, quartz	25 mg/m <sup>3</sup> (Cristobalite & Tridymite) 50 mg/m <sup>3</sup> (Quartz & Tripoli)	Not available.	Oral 500 mg/kg, rat

Calculated overall Chemical Acute Toxicity Values		
LC50 (inhalation)	LD50 (oral)	LD50 (dermal)
> 5 mg/L 4h, rat	> 2000 mg/kg, rat	> 2000 mg/kg, rabbit

Ingredient	Chemical Listed as Carcinogen or Potential Carcinogen (NTP, IARC, OSHA, ACGIH, CP65)*
Isopropanol	G-A4, I-3
Petroleum gases, liquefied, sweetened	Not listed.
Acetone	G-A4
Ceramic materials and wares, chemicals	Not listed.
Talc	G-A4, I-3
Silica, crystalline, quartz	G-A2, I-1, N-1, O, CP65

\* See Section 15 for more information.

### 11.2 DELAYED, IMMEDIATE, AND CHRONIC EFFECTS OF SHORT- AND LONG-TERM EXPOSURE

<b>Skin Corrosion/Irritation:</b>	Based on available data, the classification criteria are not met.
<b>Serious Eye Damage/Irritation:</b>	Causes serious eye irritation.
<b>Respiratory Sensitization:</b>	Based on available data, the classification criteria are not met.
<b>Skin Sensitization:</b>	Based on available data, the classification criteria are not met.
<b>STOT-Single Exposure:</b>	May cause drowsiness or dizziness.
<b>Chronic Health Effects:</b>	
<b>Carcinogenicity:</b>	Based on available data, the classification criteria are not met.
<b>Germ Cell Mutagenicity:</b>	Based on available data, the classification criteria are not met.
<b>Reproductive Toxicity:</b>	
<b>Developmental:</b>	Based on available data, the classification criteria are not met.
<b>Teratogenicity:</b>	Based on available data, the classification criteria are not met.
<b>Embryotoxicity:</b>	Based on available data, the classification criteria are not met.
<b>Fertility:</b>	Based on available data, the classification criteria are not met.
<b>STOT-Repeated Exposure:</b>	Causes damage to lungs through prolonged or repeated exposure.
<b>Aspiration Hazard:</b>	Based on available data, the classification criteria are not met.
<b>Toxicologically Synergistic Materials:</b>	Not available.
<b>Other Information:</b>	Not available.

## SAFETY DATA SHEET

### Section 12: ECOLOGICAL INFORMATION

#### 12.1 ECOTOXICITY

**Acute/Chronic Toxicity:** May cause long-term adverse effects in the aquatic environment.

#### 12.2 PERSISTENCE AND DEGRADABILITY

Not available.

#### 12.3 BIOACCUMULATIVE POTENTIAL

**Bioaccumulation:** Not available.

#### 12.4 MOBILITY IN SOIL

Not available.

#### 12.5 OTHER ADVERSE EFFECTS

Not available.

### Section 13: DISPOSAL CONSIDERATIONS

#### 13.1 WASTE TREATMENT METHODS

**Disposal Method:** This material must be disposed of in accordance with all local, state, provincial, and federal regulations.

**Other disposal recommendations:** Not available.

### Section 14: TRANSPORT INFORMATION

<b>DOT Ground</b>	Consumables, Limited Quantity
<b>IATA</b>	UN 1950, Aerosols, Flammable, 2.1
<b>IMDG</b>	UN 1950, Aerosols, 2.1 (Limited Quantity)

### Section 15: REGULATORY INFORMATION

#### 15.1 SAFETY, HEALTH AND ENVIRONMENTAL REGULATIONS/ LEGISLATIONS SPECIFIC FOR THE CHEMICAL

**Canada:** This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

**US:** MSDS prepared pursuant to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

**Mexico:** MSDS prepared pursuant to NOM-018-STPS-2000.

SARA Title III				
Ingredient	Section 302 (EHS) TPQ (lbs.)	Section 304 EHS RQ (lbs.)	CERCLA RQ (lbs.)	Section 313
Isopropanol	Not listed.	Not listed.	Not listed.	313
Petroleum gases, liquefied, sweetened	Not listed.	Not listed.	Not listed.	Not listed.
Acetone	Not listed.	Not listed.	5,000	Not listed.



## SAFETY DATA SHEET

Ceramic materials and wares, chemicals	Not listed.	Not listed.	Not listed.	Not listed.
Talc	Not listed.	Not listed.	Not listed.	Not listed.
Silica, crystalline, quartz	Not listed.	Not listed.	Not listed.	Not listed.

### State Regulations

**California Proposition 65:**

This product contains a chemical known to the State of California to cause cancer.

**Global Inventories:**

Ingredient	Canada DSL/NDSL	USA TSCA
Isopropanol	DSL	Yes.
Petroleum gases, liquefied, sweetened	DSL	Yes.
Acetone	DSL	Yes.
Ceramic materials and wares, chemicals	DSL	Yes.
Talc	DSL	Yes.
Silica, crystalline, quartz	DSL	Yes.

### NFPA-National Fire Protection Association:

<b>Health:</b>	2
<b>Fire:</b>	4
<b>Reactivity:</b>	0

### HMIS-Hazardous Materials Identification System:

<b>Health:</b>	2*
<b>Fire:</b>	4
<b>Physical Hazard:</b>	0

**Hazard Rating:** 0 = minimal, 1 = slight, 2 = moderate, 3 = severe, 4 = extreme

**SOURCE AGENCY CARCINOGEN CLASSIFICATIONS:**

**CP65**      **California Proposition 65**

**OSHA (O)**      **Occupational Safety and Health Administration.**

**ACGIH (G)**      **American Conference of Governmental Industrial Hygienists.**

- A1 - Confirmed human carcinogen.
- A2 - Suspected human carcinogen.
- A3 - Animal carcinogen.
- A4 - Not classifiable as a human carcinogen.
- A5 - Not suspected as a human carcinogen.

**IARC (I)**      **International Agency for Research on Cancer.**

- 1 - The agent (mixture) is carcinogenic to humans.
- 2A - The agent (mixture) is probably carcinogenic to humans; there is limited evidence of carcinogenicity in humans and sufficient evidence of carcinogenicity in experimental animals.
- 2B - The agent (mixture) is possibly carcinogenic to humans; there is limited evidence of carcinogenicity in humans in the absence of sufficient evidence of carcinogenicity in experimental animals.
- 3 - The agent (mixture, exposure circumstance) is not classifiable as to its carcinogenicity to humans.
- 4 - The agent (mixture, exposure circumstance) is probably not carcinogenic to humans.

**NTP (N)**      **National Toxicology Program.**

- 1 - Known to be carcinogens.
- 2 - Reasonably anticipated to be carcinogens.

### Section 16: OTHER INFORMATION

## SAFETY DATA SHEET

**Date of Preparation:** November 25, 2013

**Expiry Date:** November 25, 2016

**Version:** 1.1

**Revision Date:** September 9, 2015

**Disclaimer:** We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.

**Prepared by:** Nexreg Compliance Inc.  
Phone: (519) 488-5126  
[www.nexreg.com](http://www.nexreg.com)

**Prepared for:** Magnaflux

### End of Safety Data Sheet