

MATERIAL SAFETY DATA SHEET

ABBREVIATIONS: NA = NOT APPLICABLE
 ND = NOT DETERMINED
 NE = NOT ESTABLISHED

HEALTH = 1
 FLAMMABILITY = 0
 REACTIVITY = 0
 PERSONAL PROTECTION = B

SECTION 1 - PRODUCT IDENTIFICATION

PRODUCT NAME: BRITE STRIPE WHITE

PRODUCT TYPE: LATEX PAINT

PIONEER MANUFACTURING COMPANY
 4529 INDUSTRIAL PARKWAY
 CLEVELAND, OHIO 44135
 TELEPHONE: 800-877-1500

EMERGENCY TELEPHONE (800) 535-5053
 INFOTRAC

DATE PREPARED: 1/5/04

PREPARED BY: GSS

D.O.T. SHIPPING NAME NOT REGULATED

SECTION 2 - HAZARDOUS INGREDIENTS

CHEMICAL NAME:	CAS NO.	OSHA PEL	ACGIH TLV	% WT
MONOETHANOL AMINE	141-43-5	3 ppm	6 ppm	
ACRYLIC LATEX	N.A.	N.E.	N.E.	
WATER	7732-18-5	N.E.	N.E.	
CALCIUM CARBONATE	1317-65-3	5 mg/m ³ RESPIRIBLE DUST		
TITANIUM DIOXIDE	13463-67-7	5 mg/m ³ RESPIRIBLE DUST		

* SUBJECT TO REPORTING REQUIREMENTS OF SARA TITLE III SECTION 313, 40 CFR 372

SECTION 3 - PHYSICAL DATA

BOILING POINT (° F)	212	SPECIFIC GRAVITY:	1.35
VAPOR PRESSURE:	EQUAL TO WATER	MELTING POINT:	N.A.
VAPOR DENSITY:	EQUAL TO WATER	EVAPORATION RATE (BUAC=1):	EQUAL TO WATER
SOLUBILITY IN WATER:	SOLUBLE	pH:	9-10
APPEARANCE/ODOR:	WHITE, VISCOUS LIQUID, MILD LATEX ODOR		

SECTION 4 - FIRE AND EXPLOSION DATA

FLASH POINT (METHOD USED): NONE, SETAFLAMMABILITY LIMITS: LEL N.A. UEL N.A.

EXTINGUISHING MEDIA: WATER, FOAM, CARBON DIOXIDE, DRY CHEMICAL.

SPECIAL FIRE FIGHTING PROCEDURES: NONE

UNUSUAL FIRE FIGHTING AND EXPLOSION HAZARDS: CLOSED CONTAINERS MAY EXPLODE DUE TO STEAM FORMATION FROM EXPOSURE TO HIGH HEAT. USE WATER SPRAY TO COOL.

FOR CHEMICAL EMERGENCY
Call INFOTRAC
1-800-535-5053
24 Hrs. per day, 7 days per week

