



Material Safety Data Sheet

The Sherwin-Williams Co.
101 Prospect Ave. N.W.
Cleveland, OH 44115

Emergency telephone number
Information telephone number
Date of preparation

(216) 566-2917
(216) 566-2902
March 9, 1998

©1998, The Sherwin-Williams Co.

Wood Finishes

WOOD/1

					OIL STAIN	OIL BASE VARNISH	EXTERIOR VARNISH	PROMAR® FAST-DRI™ FLOOR SEALER	PROMAR® VARNISH SANDING SEALER	P E R C E N T B Y W E I G H T	
					A48 N 103 Dark Walnut	A48 N 109 Pecan	A66 F 90 Satin	A67 V 4 High Gloss	B26 V 2		B26 V 3
					A48 H 108 Provincial Oak	A48 N 111 English Oak	A66 V 91 High Gloss				
					A48 N 36 Danish Walnut	A48 N 115 Country Pine					
					A48 N 38 Fruitwood	A48 V 111 Clear Base					
— Section 2 —											
CAS No.	Hazardous Ingredients (percent by weight)	ACGIH TLV <STEL>	OSHA PEL <STEL>	Units	Vapor Pressure (mm Hg)						
107-21-1	§ Ethylene Glycol.	C 50	50	PPM	0.1	< 3% may be added due to tinting					
64742-89-8	V. M. & P. Naphtha.	300	300 <400>	PPM	12.0						
64742-88-7	Mineral Spirits. Mineral Spirits 140-Flash.	100	100	PPM	2.0 0.5	72 - 77					
108-88-3	§ Toluene.	50	100 <150>	PPM (Skin)	22.0	3					
136-52-7	Cobalt 2-Ethylhexanoate.	Not Established									
112926-00-8	Amorphous Precipitated Silica	10	6	Mg/M3	as Dust	4 in Satin only					
1333-86-4	Carbon Black.	3.5	3.5	Mg/M3		0 - 1					
§ Cobalt Compound. [% Cobalt]						0.1 [0.03] max.					
§ Zinc Compound. [% Zinc]											
Weight per Gallon (lbs.)						6.8 - 7.2					
VOC (Volatile Organic Compounds) - lbs./gal.						5.4 - 5.7					
Photochemically Reactive						No					
Flash Point (°F)						95					
DOL Storage Category						1C					
Flammability Classification (Flammable - Combustible)						Flammable					
HMIS (NFPA) Rating (health - flammability - reactivity)						2* - 3 - 0					

§ Ingredient subject to the reporting requirements of the Superfund Amendments and Reauthorization Act (SARA) Section 313, 40 CFR 372.65 C

Section 3 — Physical Data

PRODUCT WEIGHT	See TABLE	EVAPORATION RATE	Slower than Ether
SPECIFIC GRAVITY	0.81-0.89	VAPOR DENSITY	Heavier than Air
BOILING RANGE	222-416 °F	MELTING POINT	N.A.
VOLATILE VOLUME	55-89 %	SOLUBILITY IN WATER	N.A.

Section 4 — Fire And Explosion Hazard Data

FLAMMABILITY CLASSIFICATION See TABLE LEL 0.9 UEL 7.0
See TABLE

EXTINGUISHING MEDIA

Carbon Dioxide, Dry Chemical, Foam

UNUSUAL FIRE AND EXPLOSION HAZARDS

Keep containers tightly closed. Isolate from heat, electrical equipment, sparks, and open flame. Closed containers may explode when exposed to extreme heat. Application to hot surfaces requires special precautions. During emergency conditions overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention.

SPECIAL FIRE FIGHTING PROCEDURES

Full protective equipment including self-contained breathing apparatus should be used. Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat.

Section 5 — Health Hazard Data**ROUTES OF EXPOSURE**

Exposure may be by INHALATION and/or SKIN or EYE contact, depending on conditions of use. To minimize exposure, follow recommendations for proper use, ventilation, and personal protective equipment.

ACUTE Health Hazards**EFFECTS OF OVEREXPOSURE**

Irritation of eyes, skin and respiratory system. May cause nervous system depression. Extreme overexposure may result in unconsciousness and possibly death.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

Headache, dizziness, nausea, and loss of coordination are indications of excessive exposure to vapors or spray mists.

Redness and itching or burning sensation may indicate eye or excessive skin exposure.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

None generally recognized.

EMERGENCY AND FIRST AID PROCEDURES

If INHALED: If affected, remove from exposure. Restore breathing. Keep warm and quiet.
If on SKIN: Wash affected area thoroughly with soap and water.
Remove contaminated clothing and launder before re-use.
If in EYES: Flush eyes with large amounts of water for 15 minutes. Get medical attention.
If SWALLOWED: A48 Oil Stains Only ==> Never give anything by mouth to an unconscious person.
DO NOT INDUCE VOMITING. Give conscious patient several glasses of water. Seek medical attention.
Get Medical Attention.

Other Products ==>

CHRONIC Health Hazards

Carbon Black is classified by IARC as possibly carcinogenic to humans (group 2B) based on experimental animal data, however, there is insufficient evidence in humans for its carcinogenicity.

Cobalt and cobalt compounds are classified by IARC as possibly carcinogenic to humans (group 2B) based on experimental animal data, however, there is inadequate evidence in humans for its carcinogenicity.

Ethylene Glycol is considered an animal teratogen. It has been shown to cause birth defects in rats and mice at high doses when given in drinking water or by gavage. There is no evidence to indicate it causes birth defects in humans.

Prolonged overexposure to solvent ingredients in Section 2 may cause adverse effects to the liver, urinary, cardiovascular and reproductive systems.

Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage.

Section 6 — Reactivity Data

STABILITY - Stable
CONDITIONS TO AVOID

None known.

INCOMPATIBILITY

None known.

HAZARDOUS DECOMPOSITION PRODUCTS

By fire: Carbon Dioxide, Carbon Monoxide

HAZARDOUS POLYMERIZATION - Will Not Occur

Section 7 — Spill Or Leak Procedures**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED**

Remove all sources of ignition. Ventilate and remove with inert absorbent.

WASTE DISPOSAL METHOD

Waste from these products may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers.

Incinerate in approved facility. Do not incinerate closed container. Dispose of in accordance with Federal, State, and local regulations regarding pollution.

Section 8 — Protection Information**PRECAUTIONS TO BE TAKEN IN USE**

Use only with adequate ventilation. Avoid breathing vapor and spray mist. Avoid contact with skin and eyes. Wash hands after using.

These coatings may contain materials classified as nuisance particulates (listed 'as Dust' in Section 2) which may be present at hazardous levels only during sanding or abrading of the dried film. If no specific dusts are listed in Section 2, the applicable limits for nuisance dusts are ACGIH TLV 10 mg./m³ (total dust), 3 mg./m³ (respirable fraction), OSHA PEL 15 mg./m³ (total dust), 5 mg./m³ (respirable fraction).

VENTILATION

Local exhaust preferable. General exhaust acceptable if the exposure to materials in Section 2 is maintained below applicable exposure limits. Refer to OSHA Standards 1910.94, 1910.107, 1910.108.

RESPIRATORY PROTECTION

If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in Section 2.

When sanding or abrading the dried film, wear a dust/mist respirator approved by NIOSH/MSHA for dust which may be generated from this product, underlying paint, or the abrasive.

PROTECTIVE GLOVES

Wear gloves which are recommended by glove supplier for protection against materials in Section 2.

EYE PROTECTION

Wear safety spectacles with unperforated sideshields.

Section 9 — Precautions**DOL STORAGE CATEGORY - See TABLE****PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING**

Keep away from heat and open flame. During use and until all vapors are gone: Keep area ventilated - Do not smoke - Extinguish all flame, pilot lights, and heaters - Turn off stoves, electrical tools and appliances, and any other sources of ignition.

Consult NFPA Code. Use approved Bonding and Grounding procedures.

Keep container closed when not in use. Transfer only to approved containers with complete and appropriate labeling. Do not take internally. Keep out of the reach of children.

OTHER PRECAUTIONS

Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal.

Section 10 — Other Regulatory Information**CALIFORNIA PROPOSITION 65**

WARNING: A48H108, A48N36, A48N38, A48N103, A48N109, A48N111, A48N115, and A48V111 contain chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. A66F90, B26V2, and B26V3 contain a chemical known to the State of California to cause cancer.

TSCA CERTIFICATION

All chemicals in these products are listed, or are exempt from listing, on the TSCA Inventory.

This Material Safety Data Sheet conforms to the Hazard Communication standard, 29 CFR 1910.1200(g)(4), for similar complex mixtures.

The above information pertains to these products as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to these products may substantially alter the composition and hazards of the products. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.