

Material Safety Data Sheet

This MSDS is prepared in accordance with OSHA 29 CFR 1910.1200



WHMIS Class E: Corrosive liquid.

HCS CLASS: Toxic.

HCS CLASS: Corrosive liquid.

WHMIS (Pictograms)

WHMIS (Classification)

HCS

ζ																							

Product Name/ Trade name	AX-It	Code	099
Synonym	Baseboard Cleaner and Stripper	CAS#	Not applicable.
Chemical Family	Not available.	Validation D	ate 3/2/2007
Chemical Formula	Not applicable.	Print Date	3/23/2007
Manufacturer/ Supplier	Betco Corporation 1001 Brown Avenue Toledo, Ohio 43607 (419) 241-2156	In Case of Emergency	Chemtrec (800) 424-9300
TSCA	TSCA Inventory: All components listed or are exempt from listing		
DSL/ NDSL	All components listed unless noted elsewhere on this MSDS		Protective Clothing

Section 2. Composition an	d Information	on Ingred	lients
Nama	CAS#	9/. by	Fv

Name	CAS#	% by Weight	Exposure Limits	LCs ₀ /LD ₅₀
Water 2-Butoxyethanol	7732-18-5 111-76-2	0-100 10-15	Not available. TWA: 25 (ppm) TWA: 50 (ppm) from OSHA (PEL)	Not available. ORAL (LD50): Acute: 1746 mg/kg [Rat]. GAS (LC50): Acute: 926 ppm 4 hour(s) [Mouse].
Monoethanolamine	141-43-5	5-10	TWA: 3 (ppm) TWA: 6 (ppm) from OSHA (PEL)STEL: 6 (ppm)	Not available.
Liquified Petroleum Gas	68476-85-7	5-10	TWA: 1000 (ppm) TWA: 1000 (ppm) from OSHA (PEL)	Not available.
Xanthan Gum	11138-66-2	0-5	Not available.	ORAL (LD50): Acute: 5000 mg/kg [Rat].
Ethylene Glycol	107-21-1	0-5	Not available.	Not available.
Sodium Benzoate	532-32-1	0-5	Not available.	Not available.
Perfume Oil	N/A	0-5	Not available.	Not available.

Section 3. Hazards Identification

Potential Acute Health Effects

Corrosive to eyes and skin. Irritating to nose, throat and mouth.

Effects

Potential Chronic Health Prolonged exposure may result in skin burns and ulcerations. Severe over-exposure can produce choking, unconsciousness. May aggravate existing respiratory conditions such as

> The following information is applicable to animal data and relevance to humans has yet to be determined: Repeated or prolonged exposure to the substance can produce kidney damage.(Monoethanolamine, 2-Butoxyethanol) Repeated or prolonged exposure to the substance can produce blood disorders. (2-butoxyethanol)

Section 4. First Aid Measures								
Eye Contact	Avoid contact with eyes. Flush eyes with a gentle stream of water holding eyelids open for at least 15 minutes. Seek immediate medical attention.							
Skin Contact	In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention immediately.							
Inhalation	Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration., preferably mouth to mouth if possible.							
Ingestion	Call a poison control center immediately for treatment advice. Do NOT induce vomiting unless instructed to do so by a poison control center or doctor. Do not give anything by mouth to an unconscious person							

Section 5. Fire Fig	Section 5. Fire Fighting Measures								
Products of Combustion	Not available.								
Fire Fighting Media and Instructions	N/A								
Special Remarks on Fire Hazards	N/A								
Special Remarks on Explosion Hazards	Heated cans may burst.								

Section 6. Accide	ental Release Measures
Small Spill and Leak	Absorb with an inert material and place in an appropriate waste disposal container.
Large Spill and Leak	Absorb with an inert material and put the spilled material in an appropriate waste disposal.
Personal Protection in Case of a Large Spill	Splash goggles. Full suit. Boots. Gloves. Suggested protective clothing might not be sufficient; consult a specialist BEFORE handling this product.

Section 7. Har	Section 7. Handling and Storage								
Precautions	Avoid contact with skin and eyes. COMBUSTIBLE LIQUID AND VAPOR. DO NOT ingest.								
Incompatibility	Strong acids and oxidizers.								
Storage	Corrosive materials should be stored in a separate safety storage cabinet or room. Keep out of reach of children. For Institutional and Commercial Use								

Engineering Controls	Good general ventilation should be sufficient to control airborne levels.
Personal Protection Ey	es Splash goggles.
Во	dy Long Pants and Long Sleeves to avoid skin cotact.
Respirato	ry Wear appropriate respirator when ventilation is inadequate.
Han	ds Gloves (impervious).

Protective Clothing (Pictograms)



Exposure Limits

2-Butoxyethanol

TWA: 25 (ppm)

TWA: 50 (ppm) from OSHA (PEL)

Monoethanolamine

TWA: 3 (ppm)

TWA: 6 (ppm) from OSHA (PEL) STEL: 6 (ppm)

Liquified Petroleum Gas

TWA: 1000 (ppm)

TWA: 1000 (ppm) from OSHA (PEL)

Consult local authorities for acceptable exposure limits.

Physical State and	Liquid.	Odor	Characteristic.
Appearance		Tasts	
Molecular Weight	Not applicable.	Taste	Not available.
рН	11.5 to 12.5 [Basic.]	Color	Clear
Boiling/Condensation Point	N/A		
Melting/Freezing Point	Not available.		
Critical Temperature	Not available.		
Instability Temperature	Not available.		
Specific Gravity	Not available.		
Vapor Pressure	60 psig @ 68°F		
Vapor Density	>1 (Air = 1)		
Volatility	99		
VOC	Not available.		
Evaporation Rate	<1		
	AND AND ADDRESS OF THE PARTY OF		
Dispersion Properties	See solubility in water.		
Solubility	Easily soluble in cold water.		
The Product is:	May be combustible at high tempe	rature.	
Auto-ignition Temperature	Not available.		
Flash Points	Not available.		
Flammable Limits	LOWER: 1.1% UPPER: 17%		
Fire Hazards in Presence of Various Substances	No specific information is available in presence of various materials.	e in our database	regarding the flammability of this produced
Explosion Hazards in Presence of Various Substances	Containers may explode when hea	ted.	

Section 10. Stability and Reactivity Data								
Stability	The product is stable.							
Incompatibility with Various Substances	Strong acids and oxidizers.							
Hazardous Decomposition Products	on Will not occur.							

	cological Information
Routes of Entry	Absorbed through skin. Eye contact. Inhalation. Ingestion.
Toxicity to Animals	WARNING: THE LC50 VALUES HEREUNDER ARE ESTIMATED ON THE BASIS OF A 4-HOUR EXPOSURE. Acute oral toxicity (LD50): 1746 mg/kg [Rat]. (2-Butoxyethanol). Acute toxicity of the gas (LC50): 926 ppm 4 hour(s) [Mouse]. (2-Butoxyethanol).
Acute Effects on Huma	ns
E	yes Severe eye irritant. Liquid and mist may damage the eyes, causing corneal injury.
S	kin Severe skin irritant. May cause redness, swelling, and defatting.
Inhalat	ion Vapors may be irritating to mucous membranes of the nose, throat, and lungs. High concentrations may cause headache, dizziness, and nausea.
Ingest	ion May cause dizziness, headache, nausea, vomiting, and diarrhea. Harmful if swallowed.
Chronic Effects on Humans	Prolonged exposure may result in skin burns and ulcerations. Severe over-exposure can produce choking, unconsciousness. May aggravate existing respiratory conditions such as asthma. The following information is applicable to animal data and relevance to humans has yet to be determined: Repeated or prolonged exposure to the substance can produce kidney damage.(Monoethanolamine, 2-Butoxyethanol) Repeated or prolonged exposure to the substance can produce blood disorders. (2-butoxyethanol)
Special Remarks on Toxicity to Animals	No additional remark.
Special Remarks on Chronic Effects on Humans	No additional remark.

Section 12. Ecological Information				
Ecotoxicity	Not Available			
BOD5 and COD	Not available.			
Products of Biodegradation	Possibly hazardous short term degradation products are not likely. However, long term degradation products may arise.			
Toxicity of the Products of Biodegradation	of Not available.			
Special Remarks on the Products of Biodegradation	No additional remark.			

Section 13. Disposal Considerations			
Waste Information	Waste must be disposed of in accordance with federal, state and local environmental control regulations.		
Waste Stream	Not available.		

Section 14. Transport Information

DOT (U.S.A) (Pictograms)



TDG Classification

Not controlled under TDG (Canada).



IN UN, Proper Shipping Not applicable.

ame, PG

Maritime Transportation Not available.

Special Provisions for

Not applicable.

Transport

Section 15. Other Regulatory Information and Pictograms WHMIS Class E: Corrosive liquid. WHMIS (Classification)



Regulatory Lists No products were found.

Other Regulations OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200).

Other Classifications

HCS (U.S.A.) HCS CLASS: Toxic.

HCS CLASS: Corrosive liquid.

USA Regulatory Lists

No components found on California Prop 65

SARA 311/312 MSDS distribution - chemical inventory - hazard identification: 2-Butoxyethanol: immediate health hazard, delayed health hazard; Ethylene Glycol; Monoethanolamine; Fire; Liquified Petroleum Gas SARA 313 toxic chemical notification and release reporting:

2-Butoxyethanol; Ethylene Glycol

DSD (EEC)

International Regulations Lists No products were found.

Hazardous Material **Information System** (U.S.A.)

Health **Flammability** 0 **Physical Hazard**

3 National Fire Protection Association (U.S.A.)

Flammability Instability Health <

The Hazard Ranking systems presented on this MSDS provide only a quick reference for hazard information. The ENTIRE MSDS must be consulted to determine any specific hazards, First Aid measures, and PPE associated with this product.

Specific Hazard

Section 16. Other Information

Validated by CRushton on 3/2/2007.

Verified by CRushton.

Printed 3/23/2007.

Notice	to	Reade			

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Validated on 3/2/2007.	AX-It	Page: 6/6
Continued on Next Page		