Page: 1

OSHA PEL

COLOR PROTECT LOCKING SPRAY

Hazardous Component

*** SECTION I: General Information (Product Manufacturer) ***

CAS Reg #

PAUL MITCHELL SYSTEMS Emer. Phone: (800) 255-3924 26455 RUETHER AVENUE Info. Phone: (800) 255-3924 SANTA CLARITA CA 91350-0000 Date Prepared: 9/08/03 EPA #:

*** SECTION II: Hazardous Ingredients/Identity Information ***

7732185 DEIONIZED WATER NONE ACGIH TLV: Other: 용:

CETRIMONIUM CHLORIDE 112027 Other: ACGIH TLV: 용:

DIMETHICONE COPOLYOL PANTHENATE ACGIH TLV: Other:

*** SECTION III: Physical/Chemical Characteristics ***

Specific Gravity: NL

Method: NL Melting Point: NL

Vapor Pressure: NL
Vapor Density: >AIR
Solubility in Water: NL
Appearance and Odor: Evaporation Rate: SLOWER Boiling Point: NL

OPAQUE LIQUID, WITH NO FOREIGN MATTER, MILD FLORAL SCENT

*** SECTION IV: Fire and Explosion Hazard Data ***

Flash Point: NA F Flammable Limits: LEL NA Method: NA UEL NA

Extinguishing Methods:

FOAM, CARBON DIOXIDE, WATER FOG, SAND/EARTH

Special Fire Fighting Procedures:

USE NOISH-APPROVED SELF-CONTAINED BREATHING APPARATUS.

COOL FIRE-EXPOSED CONTAINERS WITH WATER SPRAY

Unusual Fire and Explosion Hazards:

IRRITATING OR TOXIC GASES, FUMES, SMOKES OR PARTICULATES. UNUSUAL
FIRE OR EXPLOSION HAZARDS ARE NOT EXPECTED. RELATIVE HAZARD IS

ANTICIPATED TO BE THE SAME AS NORMAL COMBUSTIBLE MATERIALS.

*** SECTION V: Reactivity Data ***

Stability: Stable Corrosive? Polymerization?

Conditions to Avoid: EXCESSIVE HEAT

*** SECTION V: Reactivity Data *** (cont.)

Incompatibility: HEAT, STRONG OXIDIZING AGENTS Hazardous Decomposition or Byproducts: CARBON MONOXIDE, CARBON DIOXIDE, SULFER OXIDES

Hazardous Polymerization:

WILL NOT OCCUR

Polymerization Conditions:

EXCESSIVÉ HEAT

*** SECTION VI: Health Hazard Data ***

Route(s) of Entry: Inhalation? Skin? Y Eye? Y Ingestion? Y

IARC Monographs? OSHA Regulated? Carcinogenicity: NTP?

Health Hazards (Acute and Chronic):

HEALTH EFFECTS: ACUTE PHYSICAL EFFECTS: NONE

Signs and Symptoms of Exposure:
MAY IRRITATE EYES
MAY IRRITATE EXISTING SKIN CONDITION ON REPEATED OR PROLONGED EXPOSURE.

EXPOSURE.

MAY CAUSE NAUSEA, VOMITING OR DIARRHEA

Medical Conditions Aggravated by Exposure:

EXISTING SKIN CONDITION CAN BE AGGRAVATED

Emergency and First Aid Procedures:

EYES:FLUSH WITH COPIOUS AMOUNTS OF WATER FOR 15 MINUTES.IF

SYMPTOMS PERSIST GET MEDICAL ATTENTION.

SKIN:REMOVE EXCESS MATERIAL AND FLUSH AFFECTED SKIN WITH WATER.

GENTLY DRY AREA WITH A CLEAN TOWEL. IF IRRITATION PERSISTS.GET

MEDICAL ATTENTION.

INHALATION:REMOVE TO UNCONTAMINATED AREA IF NOT BREATHING GIVE INHALATION: REMOVE TO UNCONTAMINATED AREA. IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION. IF BREATHING IS DIFFICULT, GIVE OXYGEN. INGESTION: IF CONSCIOUS GIVE 3-4 GLASSES OF WATER TO INDUCE VOMITING. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS OR

CONVULSING PERSON.GET MEDICAL ATTENTION.

*** SECTION VII: Precautions for Safe Handling and Use ***

Steps to be Taken in Case Material is Released or Spilled: FLOORS MAY BE SLIPPERY.
ABSORB LARGE SPILLS WITH MATERIAL SUCH AS SAWDUST, EARTH, OR SAND.
Waste Disposal Method:
SWEEP UP AND DISPOSE OF IN ACCORDANCE WITH FEDERAL STATE AND LOCAL REGULATIONS.

Precautions to be Taken in Handling and Storage: STANDARD CGMP INDICATED

Other Precautions:

10/18/06 BSG USA MSDS # 02717 Material Safety Data Sheet

*** SECTION VIII: Control Measures ***

Ventilation? Pressurized? Container Type:

Respiratory Protection:
NIOSH/MSHA APPROVED CARTIDGE RESPIRATOR TO MAINTAIN PEL/TLV
Ventilation:

Page: 3

NL

Protective Gloves:
PROTECTION GLOVES SHOULD BE WORN.

Eye Protection:
GOGGLES WHEN POURING OR WHEN SPLASHING CAN OCCUR.
Work/Hygienic Practices:

NL

This MSDS covers these requested SKUs:

SKU SIZE

DESCRIPTION

570944 8.5 OZ. PM COLOR PROTECT LOCKING SPRAY