Page: 1

Dry Wax

*** SECTION I: General Information (Product Manufacturer) ***

PAUL MITCHELL SYSTEMS
26455 RUETHER AVENUE

SANTA CLARITA
CA 91350-0000

EPA #:

Emer. Phone: (661) 298-0400
Info. Phone: () Date Prepared: 2/20/03
H=Haz/O=ORM-D:

*** SECTION II: Hazardous Ingredients/Identity Information ***

CAS Req # OSHA PEL Hazardous Component

None ACGIH TLV: Other: 용:

*** SECTION III: Physical/Chemical Characteristics ***

Specific Gravity: nl

Method: nl Melting Point: nl Vapor Pressure: nl Me
Vapor Density: Heavy Ev
Solubility in Water: nl Bo
Appearance and Odor:
Smooth hard wax with mild floral odor. Evaporation Rate: Slow Boiling Point: nl

*** SECTION IV: Fire and Explosion Hazard Data ***

Flash Point: nl F Flammable Limits: LEL nl Method: nl UEL nl

Extinguishing Methods:

Extinguishing Methods:
Foam, carbon dioxide, water fog, sand/earth
Special Fire Fighting Procedures:
Use NIOSH-approved self contained breathing apparatus. Cool
fire-exposed containers with water spray.
Unusual Fire and Explosion Hazards:
Irritating or toxic gases, fumes, smokes or particulates. Unusual
fire or explosion hazards are not expected. Relative hazard is
anticipated to be the same as normal combustible materials.

*** SECTION V: Reactivity Data ***

Stability: Stable Corrosive? Polymerization?

Conditions to Avoid:

Excessive heat

Incompatibility:

Heat, strong oxidizing agents

Hazardous Decomposition or Byproducts:
Carbon monoxide, carbon dioxide, sulfer oxides
Hazardous Polymerization:

Will not occur

Page: 2

*** SECTION V: Reactivity Data *** (cont.)

Polymerization Conditions:

Excessive heat.

*** SECTION VI: Health Hazard Data ***

Route(s) of Entry: Inhalation? N Skin? Y Eye? Y Ingestion? Y IARC Monographs? OSHA Regulated? Carcinogenicity: NTP?

Health Hazards (Acute and Chronic):
Acute: Yes Chronic: No (No specific information listed)
Signs and Symptoms of Exposure:
May irritate eyes. May irritate existing skin condition on repeated or prolonged exposure. May cause nausea, vomiting or diarrhea.

Medical Conditions Aggravated by Exposure:

Existing skin conditions aggravated by Exposure:

Existing skin condition can be aggravated.

Emergency and First Aid Procedures:

Eyes: Flush with copious amounts of water for 15 minutes. If symptoms persist get medical attention.

Skin: Remove excess material and flush affected skin with water. Gently dry area with a clean towel. If irritation persists. Get medical attention.

The lation: Remove to uncontaminated area.

Inhalation: Remove to uncontaminated area. If not breathing, give artificial respiration. If breathing is difficult, give oxygen.

Ingestion: If conscious give 3-4 glasses of water to induce vomiting. Never give anything by mouth to an unconscious or convulsing person. Get medical attention.

*** SECTION VII: Precautions for Safe Handling and Use ***

Steps to be Taken in Case Material is Released or Spilled: Floors may be slippery. Absorb large spills with material such as sawdust, earth or sand. Sweep up and dispose of in accordance with federal, state and local regulations.

Waste Disposal Method:
This material is not classified as an equitable hazardous waste. Use disposal methods consistent with federal, state and local regulations.

regulations.

Precautions to be Taken in Handling and Storage:

Other Precautions:

*** SECTION VIII: Control Measures ***

Ventilation? Container Type: Pressurized? Respiratory Protection: NIOSH/MSHA approved cartridge respirator to maintain PEL/TLV. Ventilation:

nl

BSG USA 10/18/06 MSDS # 02093 Material Safety Data Sheet

Page: 3

*** SECTION VIII: Control Measures *** (cont.)

Protective Gloves: Protection gloves.

Eye Protection:
Goggles when pouring or when splashing can occur.
Work/Hygienic Practices:

nl

This MSDS covers these requested SKUs:

SKU

SIZE

DESCRIPTION

570226

1.8 OZ

PM DRY WAX
