

**U.S. DEPARTMENT OF LABOR**  
**WAGE AND LABOR STANDARDS ADMINISTRATION**  
Bureau of Labor Standards

# MATERIAL SAFETY DATA SHEET

SECTION I	
MANUFACTURER'S NAME <b>S &amp; S Chemical Corporation</b>	EMERGENCY TELEPHONE NO.
ADDRESS (Number, Street, City, State, and ZIP Code) <b>1550 South Indiana Ave. Chicago, Illinois 60605</b>	
CHEMICAL NAME AND SYNONYMS	TRADE NAME AND SYNONYMS <b>Graffiti Spray Away</b>
CHEMICAL FAMILY <b>Solvent and detergent mixture</b>	FORMULA

SECTION II. HAZARDOUS INGREDIENTS					
PAINTS, PRESERVATIVES, & SOLVENTS	%	TLV (Units)	ALLOYS AND METALLIC COATINGS	%	TLV (Units)
PIGMENTS			BASE METAL		
CATALYST			ALLOYS		
VEHICLE			METALLIC COATINGS		
SOLVENTS <b>Isopropanol</b>	<b>10</b>	<b>400</b>	FILLER METAL PLUS COATING OR CORE FLUX		
ADDITIVES			OTHERS		
OTHERS					
HAZARDOUS MIXTURES OF OTHER LIQUIDS, SOLIDS, OR GASES				%	TLV (Units)

SECTION III. PHYSICAL DATA			
BOILING POINT (°F.) (IBP)	<b>180</b>	SPECIFIC GRAVITY (H <sub>2</sub> O=1)	<b>0.98</b>
VAPOR PRESSURE (mm Hg.) (initial)	<b>30</b>	PERCENT VOLATILE BY VOLUME (%)	
VAPOR DENSITY (AIR=1)		EVAPORATION RATE (Butyl acetate =1)	<b>initial</b>
SOLUBILITY IN WATER	<b>Emulsifies</b>		<b>2.8</b>
APPEARANCE AND ODOR	<b>Pleasant, aromatic odor, clear liquid</b>		

SECTION IV. FIRE AND EXPLOSION HAZARD DATA			
FLASH POINT (Method used)	<b>96°F TCC</b>	FLAMMABLE LIMITS	Let Uel
EXTINGUISHING MEDIA	<b>Water fog, CO<sub>2</sub>, dry chemical</b>		
SPECIAL FIRE FIGHTING PROCEDURES			
UNUSUAL FIRE AND EXPLOSION HAZARDS	<b>None</b>		

### SECTION V HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE

EFFECTS OF OVEREXPOSURE May be absorbed through skin. Overexposure to skin or inhalation of vapor may result in central nervous system depression and respiratory failure. Ingestion may produce severe irritation of gastro intestinal tract

EMERGENCY AND FIRST AID PROCEDURES  
 Flush eyes with clean water for 15 minutes. Call a physician. Flush skin with large amounts of water. Remove saturated clothing. Ingestion: Induce vomiting and call physician

### SECTION VI REACTIVITY DATA

STABILITY	UNSTABLE		CONDITIONS TO AVOID
	STABLE	X	
INCOMPATIBILITY (Materials to avoid) Strong oxidizing agents, strong mineral acids			
HAZARDOUS DECOMPOSITION PRODUCTS --			
HAZARDOUS POLYMERIZATION	MAY OCCUR		CONDITIONS TO AVOID
	WILL NOT OCCUR	X	

### SECTION VII SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED	Apply absorbent floor compounds - supply adequate ventilation - avoid heat and flames
WASTE DISPOSAL METHOD	controlled incineration

### SECTION VIII SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION (Specify type) Not needed if adequate ventilation is maintained		
VENTILATION X	LOCAL EXHAUST X	SPECIAL
	MECHANICAL (General) X	OTHER
PROTECTIVE GLOVES	EYE PROTECTION X	
OTHER PROTECTIVE EQUIPMENT		

### SECTION IX SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING	Keep away from heat and flames. Avoid prolonged contact with skin. Keep from eyes
OTHER PRECAUTIONS	