

**M A T E R I A L   S A F E T Y   D A T A   S H E E T****TRANSFER GRAPHITE BLACK**

Page: 1

PRODUCT NAME: TRANSFER GRAPHITE BLACK  
 PRODUCT CODE: 795980

HMIS CODES: H F R P  
 2 3 0 G

===== SECTION I - MANUFACTURER IDENTIFICATION =====

MANUFACTURER'S NAME: GOTHAM INK COMPANY  
 ADDRESS : 19 KAY FRIES DRIVE  
 STONY POINT, NY 10980  
 INTERNATIONAL EMERGENCY#011-813-979-0626  
 CHEMTEL EMERGENCY : 1-888-255-3924      DATE PRINTED : 10/16/12  
 INFORMATION PHONE : 1-845-947-4000      NAME OF PREPARER : JOSEPH CLOHOSEY

===== SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION =====

REPORTABLE COMPONENTS	CAS NUMBER	VAPOR PRESSURE mm Hg @ TEMP	WEIGHT PERCENT
N-PROPANOL OSHA TLV: 200 PPM, ACGIH TWA: 200 PPM. OTHER: NA	71-23-8	13.00000 68 F.	53
ETHANOL OSHA: 1000 PPM TWA, ACGIH: 1000 PPM TWA	64-17-5	40.00000 66 F.	6

\*\*\* No toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372 are present. \*\*\*  
 SHIPPING CLASSIFICATION: FLAMMABLE INK, 3.3, UN 1210

===== SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS =====

BOILING RANGE: N/A      SPECIFIC GRAVITY (H2O=1): 1.02  
 VAPOR DENSITY: HEAVIER THAN AIR      EVAPORATION RATE: < N-BUTYL ACETATE  
 COATING V.O.C.: 5.09 lb/gl      MATERIAL V.O.C.: 5.09 lb/gl  
 SOLUBILITY IN WATER: Not soluble  
 APPEARANCE AND ODOR: Colored liquid / typical solvent odor  
 \* Varnish, Topcoat & Extender have Clear to Amber or Offwhite appearance.

===== SECTION IV - FIRE AND EXPLOSION HAZARD DATA =====

FLASH POINT: <100 deg F      METHOD USED: TCC  
 FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: 2.10000      UPPER: 21.20000

EXTINGUISHING MEDIA: FOAM, CO2, DRY CHEMICAL, WATER FOG

**SPECIAL FIREFIGHTING PROCEDURES**

Self-contained breathing apparatus with full face piece operated in pressure demand or other positive pressure mode. During emergency conditions over exposure to decomposition products may cause immediate or delayed health hazards.

**UNUSUAL FIRE AND EXPLOSION HAZARDS**

Vapors are heavier than air and may travel along the ground and be ignited by heat open flame or other ignition sources. Keep containers tightly closed. Isolate from heat, sparks, electrical equipment, and open flames. Closed containers may polymerize and explode when exposed to extreme heat.

===== SECTION V - REACTIVITY DATA =====

STABILITY: STABLE  
 CONDITIONS TO AVOID

Do not expose to high temperatures or open ignition sources.

**M A T E R I A L   S A F E T Y   D A T A   S H E E T****TRANSFER GRAPHITE BLACK**

Page: 2

**INCOMPATIBILITY (MATERIALS TO AVOID)**

Avoid contact with strong oxidizing agents.

**HAZARDOUS DECOMPOSITION OR BYPRODUCTS**

May form toxic materials, carbon dioxide, carbon monoxide, various hydrocarbons, etc on thermal decomposition.

**HAZARDOUS POLYMERIZATION: WILL NOT OCCUR****===== SECTION VI - HEALTH HAZARD DATA =====**

N/A

**INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE**

Excessive inhalation of vapors can cause nasal and respiratory irritation, weakness, dizziness, fatigue, nausea, headache and possible unconsciousness. Very severe exposure may cause respiratory depression and possible convulsions.

**SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE**

Prolonged or repeated skin contact can cause moderate irritation, defatting, dermatitis. May cause pain and severe eye irritation soon as excess tearing, redness and blurred vision.

**SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE**

Organic solvents are easily absorbed; drying of the skin, redness or dermatitis are signs of repeated or overexposure to the solvents; defatting action.

**INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE**

Can cause moderate gastrointestinal irritation, nausea, vomiting &amp; diarrhea, incoordination and general weakness. May cause kidney &amp; liver damage.

**HEALTH HAZARDS (ACUTE AND CHRONIC)**

ACUTE-EYES: Can cause severe irritation, redness, tearing, and blurred vision. SKIN: Can cause severe irritation, defatting and dermatitis. INHALATION: Can cause nasal and respiratory irritation. Aspiration into lungs can cause chemical pneumonitis which can be fatal. CHRONIC: Very prolonged or repeated exposure above TLV may result in permanent brain &amp; nervous system damage.

**CARCINOGENICITY: NTP CARCINOGEN: No IARC MONOGRAPHS: No OSHA REGULATED: No**  
None known at this time.**MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE**

Prolonged or exposure to very high concentrations of vapors may aggravate existing dermatitis or produce blood disorders

**EMERGENCY AND FIRST AID PROCEDURES**

EYES: Flush immediately with large amounts of water for at least 15 minutes. Take to a physician for medical treatment SKIN: Wash affected areas with soap and water. Remove contaminated clothing. Consult a physician if irritation persists. INHALATION: Remove to fresh air. Restore breathing. Treat symptomatically. Consult a physician. INGESTION: Drink 1 or 2 glasses of water to dilute. Do not induce vomiting. Consult a physician or poison control center immediately. Treat symptomatically.

**===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====****STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED**

Eliminate all ignition sources. Dike, contain, or absorb with inert materials (sand, vermiculite, etc.). Transfer to containers for recovery or disposal. Prevent runoff into sewers, streams, or other bodies of water. GROUND WORK EQUIPMENT.

**WASTE DISPOSAL METHOD**

Dispose of in accordance with all local, state, or Federal regulations.

**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING**

Do not store or use near sources of high temperatures, near fire or open flame, or other ignition sources. Keep container close. NOTE: ALL CONTAINERS MUST BE GROUNDED AND BONDED WHEN POURING.

M A T E R I A L   S A F E T Y   D A T A   S H E E T

TRANSFER GRAPHITE BLACK

Page: 3

**OTHER PRECAUTIONS**

Do not take internally. Avoid prolonged or repeated exposure to levels above TLV. Hot organic chemical vapors or mists are susceptible to sudden spontaneous combustion when mixed with air. Ignition may occur at typical elevated-temperature process conditions. Any proposed use of this product in elevated-temperature processes should be thoroughly evaluated to assure that safe operating conditions are established and maintained.

## ===== SECTION VIII - CONTROL MEASURES =====

**RESPIRATORY PROTECTION**

If TLV is exceeded use NIOSH/MSHA approved organic vapor and mist, supplied air or self contained breathing apparatus.

**VENTILATION**

Use adequate mechanical (general and/or local) ventilation to maintain exposure below TLV. Special local ventilation is recommended at points where vapors can be expected to escape to the workplace air.

**PROTECTIVE GLOVES**

Wear resistant gloves such as nitrile rubber.

**EYE PROTECTION**

Use chemical splash goggles or other OSHA permitted safety glasses.

**OTHER PROTECTIVE CLOTHING OR EQUIPMENT**

Wear impervious clothing. Eyewash stations.

**WORK/HYGIENIC PRACTICES**

Wash hands before eating or using restrooms. Remove and wash contaminated clothing before reuse.

## ===== SECTION IX - DISCLAIMER =====

The information contained herein is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees.