# Varn International, Inc., a Flint Group Company

14909 N. Beck Road Plymouth, MI 48180

For Product Questions call: (800) 336-VARN(8276) For Health and Safety Questions call: (800) 336-VARN(8276)

After Hours Emergency Health/Safety Questions: (800) 391-0698 Prosar (US/Canada) 24 Hour Emergency Spill Contact call: (800) 424-9300 Chemtrec (US/Canada)

# **Material Safety Data Sheet**

#### I. PRODUCT AND COMPANY IDENTIFICATION

Product Name: CALIFORNIA WASH Product Code: 650-B010002

MSDS Code: MSD-00939942

Revision Number:

**Revision Date:** 2011-02-25 16:30:53

#### II. COMPOSITION/INFORMATION ON INGREDIENTS

| CAS#       | Chemical Name   | %         |
|------------|---|-----------|
| 64742-47-8 | Hydrotreated Light Distillate (Petroleum)                 | 60 - 90   |
| 34590-94-8 | Dipropylene Glycol Monomethyl Ether                       | 7 - 13    |
| 64742-95-6 | Solvent naphtha (petroleum), light arom.                  | 1 - 5     |
| 94266-47-4 | Citrus Terpenes   | 1 - 5     |
| 95-63-6    | 1,2,4-Trimethylbenzene                                    | 1 - 5     |
| 68412-54-4 | Poly (oxy,-ethanediyl), -(nonylphenyl)-hydroxy-, branched | 1 - 5     |
| 108-67-8   | 1,3,5-Trimethylbenzene                                    | 0.5 - 1.5 |

Please see Section VIII for product and component exposure guidelines.

Components not listed are not physical or health hazards as defined in 29 CFR 1910.1200 (Hazard Communication Standard).

#### **III. HAZARDS IDENTIFICATION**

HMIS Rating Health: 1 Flammability: 2 Reactivity: 0

## This product falls under the following WHMIS class:

ВЗ

Routes of Entry: Inhalation, Ingestion, Skin contact, Eye contact

Target Organs: Eyes, Central Nervous System, Respiratory Tract, Lungs, Skin, Blood

**Medical Conditions** Eye disease, Respiratory disease including asthma and bronchitis, Lung disease,

**Aggravated**: Skin disease including eczema and sensitization

## Immediate (Acute) Health Effects by Route of Exposure

**Inhalation:** Can cause moderate respiratory irritation, dizziness, weakness, fatigue, nausea

and headache. Inhalation of high concentrations may result in central nervous system (CNS) effects such as dizziness, weakness, fatigue, nausea, headache,

and lack of coordination.

**Skin Contact:** Can cause minor skin irritation, defatting, and dermatitis.

**Eye Contact:** Can cause moderate irritation, tearing and reddening, but not likely to

permanently injure eye tissue.

**Ingestion:** Irritating to mouth, throat, and stomach. Can cause abdominal discomfort,

nausea, vomiting and diarrhea. Aspiration of material into the lungs can cause chemical pneumonitis. Harmful if swallowed. May cause systemic poisoning.

**Long-Term (Chronic) Health Effects** 

Reproductive and

No data available to indicate product or any components present at greater than

**Developmental:** 

0.1% may cause birth defects.

Mutagenicity:

No data available to indicate product or any components present at greater than

0.1% is mutagenic or genotoxic.

Inhalation:

Upon prolonged and/or repeated exposure, can cause minor respiratory irritation, dizziness, weakness, fatigue, nausea, and headache.Harmful! Can

cause systemic damage upon prolonged and/or repeated exposure.

**Skin Contact:** 

Upon prolonged or repeated contact, can cause minor skin irritation, defatting, and dermatitis. Upon prolonged or repeated exposure, harmful if absorbed

through the skin. May cause minor systemic damage.

Ingredients of this product appear on the following OSHA identified carcinogen lists at >= 0.1% by

weight (yes/no): OSHA No

NTP No

IARC 1 & 2A No IARC 2B No NIOSH No

#### **IV. FIRST-AID MEASURES**

**Inhalation:** Remove to fresh air. If breathing is difficult, have a trained individual administer

oxygen. If not breathing, give artificial respiration and have a trained individual

administer oxygen. Get medical attention immediately.

**Eyes:** Immediately flush eyes with plenty of water for at least 20 minutes retracting

eyelids often. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Get immediate medical attention and monitor the eye as

advised by your physician.

**Skin Contact:** Wash with soap and water. Remove contaminated clothing and launder. Get

medical attention if irritation develops or persists.

**Ingestion:** Do not induce vomiting and seek medical attention immediately. Drink two

glasses of water or milk to dilute. Provide medical care provider with this MSDS. Induce vomiting as a last measure. Induced vomiting may lead to aspiration of the

material into the lungs potentially causing chemical pneumonitis.

## **V. FIRE FIGHTING MEASURES**

**Flammability** Combustible NFPA II (NFPA description only; not to be used for shipping

**Summary:** purposes)

Extinguishing Media: Use alcohol resistant foam, carbon dioxide, or dry chemical extinguishing

agents. Water may be ineffective but water spray can be used to extinguish a fire if swept across the base of the flames. Water can absorb heat and keep

exposed material from being damaged by fire.

Fire and/or Explosion

Hazards:

Vapors may be ignited by sparks, flames or other sources of ignition if material is above the flash point giving rise to a fire (Class B). Vapors are heavier than air

and may travel to a source of ignition and flash back.

Fire Fighting Methods and Protection:

Do not enter fire area without proper protection including self-contained breathing apparatus and full protective equipment. Fight fire from a safe

distance and a protected location due to the potential of hazardous vapors and decomposition products. Flammable component(s) of this material may be

lighter than water and burn while floating on the surface.

Hazardous Carbon dioxide, Carbon monoxide

Combustion Products:

**Flash Point:** 38 C (100 F) - 60 C (140F) Firepoint: Firepoint not determined.

Upper Flammable/Explosive Limit, % in air: 6.2 Lower Flammable/Explosive Limit, % in air: 1.1

#### VI. ACCIDENTAL RELEASE MEASURES

Personal Precautions and Equipment:

Exposure to the spilled material may be irritating or harmful. Follow personal protective equipment recommendations found in Section VIII of this MSDS. Additional precautions may be necessary based on special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred. Also consider the expertise of employees in the area responding to the spill.

## **VII. HANDLING AND STORAGE**

Product Use: Press Wash

**Handling** Harmful or irritating material. Avoid contacting and avoid breathing the material.

**Precautions:** Use only in a well ventilated area. Ground and bond containers when

transferring material Avoid contact with material, avoid breathing dusts or fumes,

use only in a well ventilated area.

**Storage Conditions:** Store in a cool dry place. Isolate from incompatible materials. Do not store in

direct sunlight. Keep away from heat, sparks, and flame. Store in a tightly closed

container.

#### **VIII. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Engineering** Local exhaust ventilation or other engineering controls are normally required

**Measures:** when handling or using this product to avoid overexposure.

**Respiratory** General or local exhaust ventilation is the preferred means of control. If general

**Protection:** or local exhaust ventilation is not available or sufficient to control or eliminate

symptoms as described in Section III, respiratory protection should be used.

Eye Protection: Wear safety glasses with side shields when handling this product. Wear

additional eye protection such as chemical splash goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid. or

airborne material. Have an eye wash station available.

**Skin Protection:** Not normally considered a skin hazard. Where use can result in skin contact.

practice good personal hygiene and wear a barrier cream and/or impervious surgical style gloves. Wash hands and other exposed areas with mild soap and

water before eating, drinking, and when leaving work.

Gloves: Wear impervious material. Butyl rubber or Nitrile

## **Exposure Guidelines:**

| CAS#       | Chemical Name                             | OSHA Exposure Limits   | ACGIH TLV -<br>TWA            | ACGIH<br>STEL                      | IDLH            |
|------------|---|--|-------------------------------|------------------------------------|-----------------|
| 64742-47-8 | Hydrotreated Light Distillate (Petroleum) |  | No TLV                        | No STEL                            | Not on list     |
| 34590-94-8 | Dipropylene Glycol<br>Monomethyl Ether    | 100 ppm TWA; 600 mg/m3<br>TWA prevent or reduce skin<br>absorption | 100 PPM TWA; 606<br>MG/M3 TWA | 150 PPM<br>STEL; 909<br>MG/M3 STEL | 600 ppm<br>IDLH |

| 64742-95-6 | Solvent naphtha (petroleum), light arom.                   | No TLV | No STEL | Not on list |
|------------|--|--------|---------|-------------|
| 94266-47-4 | Citrus Terpenes  | No TLV | No STEL | Not on list |
| 95-63-6    | 1,2,4-<br>Trimethylbenzene                                 | No TLV | No STEL | Not on list |
| 68412-54-4 | Poly (oxy,-ethanediyl), -(nonylphenyl)- hydroxy-, branched | No TLV | No STEL | Not on list |
| 108-67-8   | 1,3,5-<br>Trimethylbenzene                                 | No TLV | No STEL | Not on list |

If this product is provided in a dry powder state it should be considered a nuisance dust (PEL 10 mg/m3).

If the processing of this product produces a mist it should be considered to be an oil mist with a PEL of 5 mg/m3.

## IX. PHYSICAL AND CHEMICAL PROPERTIES

**Physical State:** Liquid Color: Yellow Odor: Petroleum or solvent Solubility in Water: **Emulsifies** Vapor Pressure (mmHg @ 20 deg. C): 2.5 **Volatile Organic Chemicals % by wt:** 98.1 VOC lb/gal 6.53 **Specific Gravity:** 8.0

Specific Gravity: 0.8

Bulk Density (lbs/Gal): 6.66

Bulk Density (kg/L): 0.8

# X. STABILITY AND REACTIVITY

**Stability:** Stable under normal conditions.

Conditions to Avoid: Temperatures above flash point in combination with sparks, open flames, or

other sources of ignition.

Materials to Strong oxidizing agents.

Avoid/Chemical Incompatibility:

## XI. TOXICOLOGICAL INFORMATION

| Component Toxicology Data (NIOSH): |  |   |  |  |
|------------------------------------|--|---|--|--|
| CAS#                               | Chemical Name  | LD50/LC50   |  |  |
| 64742-47-8                         | Hydrotreated Light Distillate (Petroleum)                  | No data available   |  |  |
| 34590-94-8                         | Dipropylene Glycol Monomethyl<br>Ether                     | Oral LD50 Rat 5230 mg/kg; Dermal LD50 Rabbit 9500 mg/kg   |  |  |
| 64742-95-6                         | Solvent naphtha (petroleum), light arom.                   | Inhalation LC50 Rat >5.2 mg/L 4 h; Inhalation LC50 Rat 3400 ppm 4 h; Oral LD50 Rat 8400 mg/kg; Dermal LD50 Rabbit >2000 mg/kg |  |  |
| 94266-47-4                         | Citrus Terpenes  | ORAL, RAT: LD50 = 4400 MG/KG; ORAL, MOUSE: LD50 = 5600 MG/KG; SKIN, RABBIT: LD50 = >5 GM/KG                                   |  |  |
| 95-63-6                            | 1,2,4-Trimethylbenzene                                     | ORAL, RAT: LD50 = 5 GM/KG; INHALATION, RAT: LC50 = 18 GM/M3/4H  |  |  |
| 68412-54-4                         | Poly (oxy,-ethanediyl), - (nonylphenyl)-hydroxy-, branched | No data available   |  |  |
| 108-67-8                           | 1,3,5-Trimethylbenzene                                     | Inhalation LC50 Rat 24 g/m3 4 h; Oral LD50 Rat 5000 mg/kg   |  |  |

## XII. DISPOSAL CONSIDERATIONS

**Waste Description** for Spent Product: Spent or discarded material may be a hazardous waste.

**Disposal Methods:** Dispose in accordance with Federal, State, Provincial and Local regulations.

Material may be compatible with industrial waste incineration or inclusion in a fuel blending program. This characterization is subject to approval by your waste

management contractor. This material should be recycled if possible.

## XIII. REGULATORY INFORMATION

**TSCA Status** All ingredients of this product are listed or are excluded from listing on the U.S.

Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

| Chemical Name                                   | CAS#       | Regulation | Percentage |
|---|------------|------------|------------|
| Benzene, dimethyl-                              | 1330-20-7  | CERCLA     | 0.25       |
| Benzene, (1-methylethyl)-                       | 98-82-8    | CERCLA     | 0.17       |
| Light aromatic solvent naphtha                  | 64742-95-6 | NPRI (Cdn) | 3.82       |
| 1,2,4-Trimethylbenzene                          | 95-63-6    | NPRI (Cdn) | 2.71       |
| Polyethylene glycol branched nonylphenyl ether  | 68412-54-4 | NPRI (Cdn) | 1.89       |
| Benzene, (1-methylethyl)-                       | 98-82-8    | PROP 65    | 0.17       |
| 1,2,4-Trimethylbenzene                          | 95-63-6    | SARA 313   | 2.71       |
| Nonylphenol, branched, ethoxylated (<18% Glycol | 68412-54-4 | SARA 313   | 1.89       |
| Ether)  |            |            |            |
| Xylene (mixed isomers)                          | 1330-20-7  | SARA 313   | 0.25       |
| Cumene  | 98-82-8    | SARA 313   | 0.17       |
| Not on list                                     |            | SARA EHS   |            |

## The following items require export notification for TSCA **Chemical Name**

TSCA 12b list section

Dipropylene glycol monomethyl ether

Section 4, 1 % de minimus concentration

This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulations and the MSDS contains information required by the Controlled Products Regulations.

#### XIV. TRANSPORTATION INFORMATION

49CFR/TDG - Non-bulk: GROUND SHIPMENTS NOT REGULATED IN PACKAGINGS OF 119 GAL

(450 L) OR LESS.

49CFR/TDG - Bulk: UN1993, FLAMMABLE LIQUID, N.O.S. (NAPHTHA), 3, PGIII, ERG128

LIMITED QUANTITY EXCEPTION MAY BE USED IF EACH INNER IATA - Limited Quantity:

PACKAGING IS 1.3 GAL (5 L) OR LESS. ADD "LTD QTY" TO

DESCRIPTION.

UN1993, FLAMMABLE LIQUID, N.O.S. (NAPHTHA), 3, PGIII, ERG128 IATA - Non-bulk:

UN1993, FLAMMABLE LIQUID, N.O.S. (NAPHTHA), 3, PGIII, ERG128 IATA - Bulk:

REGULATED. REFER TO BILL OF LADING. IMDG - Non-bulk:

#### XV. ADDITIONAL INFORMATION

#### References:

Disclaimer: Varn International, Inc. a Flint Group Company has prepared this Material Safety Data Sheet ("MSDS") in compliance with 29 CFR 1910.1200, understands that its customers may use this MSDS to comply with that section, and believes that the data set forth herein are accurate as of the date hereof; however, this MSDS shall not constitute a warranty with respect thereto.

CALIFORNIA WASH

