

Slick Works

\*\*\* SECTION I: General Information (Product Manufacturer) \*\*\*

PAUL MITCHELL SYSTEMS Emer. Phone: ( ) -  
26455 RUETHER AVENUE Info. Phone: (909) 598-1951  
SANTA CLARITA CA 91350-0000 Date Prepared: 3/13/02  
EPA #: H-Haz/O=ORM-D:

\*\*\* SECTION II: Hazardous Ingredients/Identity Information \*\*\*

Hazardous Component	CAS Reg #	OSHA PEL
NA		
ACGIH TLV:	Other:	%:

\*\*\* SECTION III: Physical/Chemical Characteristics \*\*\*

Specific Gravity: nl Method: nl  
Vapor Pressure: nl Melting Point: nl  
Vapor Density: >air Evaporation Rate: <ether  
Solubility in Water: nl Boiling Point: 90-100  
Appearance and Odor:  
clear to slightly hazy ringing gel

\*\*\* SECTION IV: Fire and Explosion Hazard Data \*\*\*

Flash Point: 150 F Flammable Limits: LEL na  
Method: TCC UEL na

Extinguishing Methods:

foam, CO2, water fog, sand/earth

Special Fire Fighting Procedures:

must wear NIOSH approved self contained breathing apparatus.cool  
fire-exposed containers with water supply

Unusual Fire and Explosion Hazards:

thermal decomposition may produce toxic fumes or oxides of carbon  
and nitrogen

\*\*\* SECTION V: Reactivity Data \*\*\*

Stability: Stable Corrosive? Polymerization? N

Conditions to Avoid:

heat

Incompatibility:

strong oxidizing agents

Hazardous Decomposition or Byproducts:

CO, CO2, NO

Hazardous Polymerization:

nl

Polymerization Conditions:

nl

\*\*\* SECTION VI: Health Hazard Data \*\*\*

Route(s) of Entry: Inhalation? Skin? X Eye? Ingestion? X  
Carcinogenicity: NTP? IARC Monographs? OSHA Regulated?

Health Hazards (Acute and Chronic):  
not determined  
Signs and Symptoms of Exposure:  
nl  
Medical Conditions Aggravated by Exposure:  
nl  
Emergency and First Aid Procedures:  
skin: may be irritating to extra sensitive skin, flush with water  
get medical attention if persists.  
eye: flush with copious amount of water. if irritation persists  
consult doctor  
ingestion: give 3-4 glasses of water. do not give to unconscious  
or convulsing person

\*\*\* SECTION VII: Precautions for Safe Handling and Use \*\*\*

Steps to be Taken in Case Material is Released or Spilled:  
floors may be slippery, absorb large spilled material with inert  
material. sweep up and dispose.  
Waste Disposal Method:  
use methods consistent with federal, state and local regulations  
Precautions to be Taken in Handling and Storage:  
standard GMP indicated  
Other Precautions:  
nl

\*\*\* SECTION VIII: Control Measures \*\*\*

Ventilation? N Pressurized? Container Type:  
Respiratory Protection:  
na  
Ventilation:  
na  
Protective Gloves:  
na  
Eye Protection:  
na  
Work/Hygienic Practices:  
na

This MSDS covers these requested SKUs:

SKU	SIZE	DESCRIPTION
570253	6.8 OZ	FM SLICK WORKS
570275	10.14 OZ	FM SLICK WORKS

\*\*\*\*\*  
\*The information contained herein is based on the data available\*  
\*to us and is believed to be correct to the best of our ability.\*  
\*However, Sally Beauty Company makes no warranty, expressed or \*  
\*implied regarding the accuracy of this data nor assumes any \*  
\*responsibility for injury from the intentional or non- \*  
\*intentional misuse of this product. \*  
\*\*\*\*\*