



MATERIAL SAFETY DATA SHEET

Product Name: Electrical Stimulators
Model Number: DT3002, TENS 7000, DI1010, DI8195, DU2035, DQ8432, DQ9275, DQ7844
Date prepared: January 29, 2014

1. COMPANY IDENTIFICATION:

Manufacturer: Roscoe Medical Inc.
21973 Commerce Pkwy
Strongsville, OH. 44149

Department: Quality Department

Telephone Number: 440-572-1962

RECEIVED
JUL 28 2015
BY:

2. HEALTH HAZARD INFORMATION

GHS Classification:

This product is not hazardous under the criteria of U.S. Occupational Safety and Health Standard 29CFR 1910 Subpart Z and United Nations GHS Parts 2, 3, and 4.

Potential Health Effects:

Eye: Dust and process vapors may irritate eyes.


Skin: Exposure to molten resin may cause thermal burns.

Inhalation: Dust and process vapors may cause respiratory tract irritation.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical name: Acrylonitrile-Butadiene-Styrene Copolymer

Chemical Formula (Constitutional or Structural):



21973 Commerce Parkway
Strongsville, OH 44149

Toll free: 800-3-ROSCOE (376-7263)

main: 440-572-1962

fax: 440-572-42691

www.roscoemedical.com



MATERIAL SAFETY DATA SHEET

Ingredients and Composition: Approx. 100%
Published Reference number of Gazette: Chemical
Substances Control Law: 6-720, 6-126
CAS registry number: 09003-56-9

4. FIRST-AID MEASURES

Eye Contact:

If the product enters the eyes and the eyes are rubbed, it may cause irritation or injury to the cornea. Thus, wash with water without rubbing. Remove contact lenses immediately. In case of any abnormalities, receive the treatment of a physician.

Skin Contact:

Wash with water. If condensation of gas generated from the substance molten at high temperature comes into contact with the skin, wash well with soapy water.

Inhalation:

Judging from the shape, it is unlikely that the pellets will be inhaled. In case lots of fumes generated from high temperature molten resins are inhaled, move to a place having fresh air. In case of cough or difficulty in respiration, receive the treatment of a physician.

Ingestion:

Although this is unlikely to happen, there is no acute toxicity, even if it is swallowed. In case large amounts are swallowed, receive the treatment of a physician.

5. FIRE-FIGHTING MEASURES

Extinguishing Measures:

At the time of fire, high heats as well as gases containing dense black smoke, carbon dioxide, carbon monoxide, nitrogen oxides, etc. are generated. At the time of fire-fighting, wear proper protective clothing and respirators.

Extinguishing Media:

Water, water spray, and various kinds of fire-extinguisher may be used.

21973 Commerce Parkway
Strongsville, OH 44149

Toll free: 800-3-ROSCOE (374-7263)
main: 440-572-1962
fax: 440-572-4269

www.roscoemedical.com



MATERIAL SAFETY DATA SHEET

6. ACCIDENTAL RELEASE MEASURES

In case product is spilled on the road or floor, there is danger of slipping and falling. Thus, collect the spilled pellets and dispose of them. If it is accidentally released, it may cause environmental contamination, so immediately collect all that has been released.

7. HANDLING AND STORAGE

Handling:

The gas generated at the time of processing may irritate the respiratory organs and skin. And when inhaled in large amount, vomiting and headaches may occur in certain individuals. Thus, avoid inhalation of such gases. In the case of mechanical processing (cutting, sanding, etc.), the fine dust generated by crushing may cause dust explosion by the static electricity and electrical sparks that are generated. Thus, aim at keeping the work place clean so that dust will not accumulate.

Storage:

Store in a place which is not exposed to the direct rays of the sun, and keep away from heat or ignition sources.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Control Concentration: Not Specified

Tolerable Concentration:

Neither Japan Association of Industrial Health nor ACGIH specifies the tolerable concentration of MSDS resin dust, but it is believed that the following values are reasonable guidelines for operation.

Item	Time Weighted Average Value	
	Inhalable Dust	Total Dust
Recommendation Value of Japan Association of Industrial Health (1995) Class 3 Dust	2 mg/m ³	8 mg/m ³
Recommendation Value of ACGIH(1995 ~ 1998) (Nuisance Dust)	5 mg/m ³	10 mg/m ³

Equipment Countermeasures:

At the time of processing in high temperature, gas will be generated from the portion open to the atmosphere. Thus, in order to obtain comfortable work environment, it is desirable to install local ventilation.

21973 Commerce Parkway
Strongsville, OH 44149

Toll free: 800-3-ROSCOE (376-7263)
main: 440-572-1962
fax: 440-572-42691

www.roscoemedical.com



MATERIAL SAFETY DATA SHEET

Protective Equipment for Respiration:

In case of work which generates dust, such as mechanical processing or sanding of resin products, dust respirators shall be worn. In case of work that is done in a place having high concentration of generated gases or fumes, wear a chemical cartridge respirator (for organic chemicals).

Protective Goggles:

In case of work that generates dust such as mechanical processing or sanding of resin products, wear protective goggles made of plastic.

Protective Gloves:

When handling pellets, there is no special need of gloves. However, when handling molten resins, wear gloves that have good thermal insulation.

Protective Clothing:

Ordinary work clothing will do, but in case of handling molten resins, wear work clothing having long sleeves.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Milky Off-White Pellet Form Solids

Flashing Point: 400°C

Auto Ignition Point: 466°C

Vapor Pressure: None

Volatility: None

Melting point: There is no definite melting point, and it gradually becomes soft over a broad range (130°C~150°C)

Specific Gravity: 1.03 ~ 1.07

Solubility: Insoluble in water

10. STABILITY AND REACTIVITY

Flash point: None

Upper Explosion Limit: None

Lower Explosion Limit: None

Auto-ignitability: Auto-ignition Temperature is 466 °C (ASTM-D1929-77)

Reactivity with Water: None

21973 Commerce Parkway
Strongsville, OH 44149

Toll free: 800-3-ROSCOE (376-7263)
main: 440-572-1962
fax: 440-572-42691

www.roscoemedical.com



MATERIAL SAFETY DATA SHEET

Oxidizability: None as far as ordinary storage and handling are concerned.

Self-Reactivity / Explosiveness: Although there is no self-reactivity at normal temperature, when the temperature becomes high (280 °C~400 °C), the resin decomposes and generates decomposed gases. Thus, the molten resin shall be cooled rapidly with water.

Dust Explosiveness: Explosive

Stability / Reactivity: None, as far ordinary storage and handling are concerned.

11. TOXICOLOGICAL INFORMATION

Skin Corrosiveness: None

Irritability (Skin, Eyes): There is physical irritability

Allergenic and Sensitizing Effects: None

Acute Toxicity (Includes 50% Lethal Dose): Oral LD 50 (Rat) > 5g/kg (Assumed Value)

Sub-Acute Toxicity: No Information

Chronic Toxicity: No Information

Carcinogenic Effects: No Information

Mutagenic Effects: No information

Effects on the Reproductive System: No Information

Teratogenic Effects: No Information

Others: (Includes generation of toxic gases by reaction with water, etc.)

12. ECOLOGICAL INFORMATION

Biodegradability: Not Biodegradable

Bioaccumulation: No Information

Fish Toxicity: No Information Others: In order to prevent the marine animals and birds from ingesting it, it just not be abandoned or dumped in any ocean or water area.

13. DISPOSAL CONSIDERATIONS

Recycling, incineration or landfill. Use approved disposal methods as recommended by state and local agencies.

14. TRANSPORT INFORMATION

Avoid wetting or rough handling so that the packaging will not be damaged. In case the bags are damaged and the pellets are scattered, pay attention so that no one will slip and fall. All of the materials that have spilled shall be rapidly collected.

21973 Commerce Parkway
Strongsville, OH 44149

Toll free: 800-3-ROSCOE (376-7263)
main: 440-572-1962
fax: 440-572-42691

www.roscoemedical.com



MATERIAL SAFETY DATA SHEET

15. REGULATORY INFORMATION

The Fire Services Act of Japan Specified Flammables (3,000 kg or above)

16. OTHER INFORMATION

References: 1)

Manual for Preventing the Discharging of Resin Pellets / Japan Plastics Industry Federation
February, 1993.

The information described herein was prepared on the basis of the materials, information, and data available at the present time, and the above information may be revised by new knowledge. The precautionary items were based on ordinary handling. In case of special handling, safety measures in compliance with the application and usage shall be executed. The above was given as information, and no guarantee, express or implied, is made. Final determination of safety and suitability of any material is the sole responsibility of the keeper and user. All materials may present unknown hazards, and therefore should be handled with adequate caution. Although certain hazards are described herein, they may not be the only hazards in relation to the products.

To the best of our knowledge, the information contained herein is accurate. However, Roscoe Medical does not assume any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user.

21973 Commerce Parkway
Strongsville, OH 44149

Toll free: 800-3-ROSCOE (376-7263)
main: 440-572-1962
fax: 440-572-4269

www.roscoemedical.com