

4024

Safety Data Sheet

9719193 A-F

Section 1. Identification

Product Name: Vinyl Compound - Plastisol
Product Code: LA-261B Gray U5278E

Date Revised: 12/19/2014

Manufacturer:
Lakeside Plastics Inc.
450 W 33rd Ave.
Oshkosh, WI 54903
920-235-3620

Emergency Contact:
800-535-5053

Section 2. Hazard Identification

Emergency Overview: No immediate effects are anticipated but repeated or prolonged contact may cause eye or skin irritation.

Eye contact: May cause mild irritation.

Skin contact: Direct contact over a prolonged period may cause irritation.

Ingestion: Can cause gastrointestinal irritation.

Inhalation: Not likely to cause irritation at ambient temperatures. Heating this material will cause fumes and vapors which can cause irritation of the respiratory tract.

Section 3. Composition /Information on Ingredients

This product is not considered to be or to contain hazardous chemicals based on evaluations made by our company under the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Section 4. First Aid Measures

Eyes: Flush with large amounts of water, holding eyelid open for 15 minutes. If irritation persists, seek medical attention.

Skin: Wash with soap and water or plain water for 15 minutes. If rash or irritation develops, seek medical attention.

Inhalation: Remove to fresh air.

Ingestion: Do not induce vomiting. Never give anything by mouth to an unconscious person.

Medical Conditions Aggravated by Exposure: None known.

Section 5. Fire Fighting Measures

Flash Point: > 200 deg F

OSHA Flammability Classification: Combustible Liquid- Class IIB

Extinguishing Media: Dry chemical, carbon dioxide, foam.

Special Firefighting Procedures: Wear self-contained breathing apparatus.

Unusual Fire and Explosion Hazards: May generate HCl and oxides of carbon.

Section 6. Accidental Release Measures

Action to be taken in case of release or spill: Contain material and scoop up or soak up material with absorbent compound. See Section 13 for proper disposal methods.

Section 7. Handling and Storage

Handling: Keep away from heat and flames. Wear protective gloves and safety glasses. Do not weld or torch cut empty containers without local exhaust and/or respiratory protection.

Storage: Do not store at elevated temperatures; keep containers closed when not in use.

Section 8. Exposure Controls/ Personal Protection

Engineering Controls: Provide sufficient mechanical ventilation to maintain exposure below TLV's.

Respiratory Protective Equipment: Not normally required however if local exhaust is insufficient to remove fumes or vapors generated during processing, NIOSH approved respirators may be necessary.

Protective Gloves: Rubber, neoprene or nitrile.

Eye and Face Protection: Industrial safety glasses.

Other Protective Equipment: Use chemical resistant apron or other impervious clothing, if needed, to avoid contaminating regular clothing which could result in prolonged or repeated skin contact. An emergency shower should be readily available.

Ventilation: Local exhaust is recommended.

Section 9. Physical and Chemical Properties

Boiling Range: None

Vapor Density: Heavier than air.

Weight per Gallon: 14.45 lb +/- 0.10

Evaporation Rate: Slower than butyl acetate

% Volatile by Weight: < 2.0%

Section 10. Stability and Reactivity

Stability: Stable

Hazardous Polymerization: Will not occur.

Hazardous Decomposition Products: Hydrogen chloride and oxides of carbon.

Incompatibility: Strong oxidizers.

Conditions to Avoid: Prolonged exposure to temperatures above 300 deg F.

Section 11. Toxicological Information

Toxicity Data: None of the components in this material are listed as a carcinogen by NTP, IARC or OSHA.

Section 12. Ecological Information

Ecotoxicological Information: No data available.

Section 13. Disposal Considerations

Disposal Method: Dispose of in accordance with local, state and federal regulations.

Section 14. Transportation Information

DOT Shipping Name: Not regulated.

Section 15. Regulatory Information

TSCA Status: All components of this compound are listed on the US TSCA Inventory.

SARA Section 313 Toxic Chemicals: None

California Proposition 65: This product contains chemical(s) known to the State of California to cause cancer and/or birth defects or other reproductive harm.

Section 16. Other Information

Disclaimer of Expressed and Implied Warranties: The information in this document is believed to be correct as of the date issued. However, no warranty of fitness for any particular purpose, or any other warranty is expressed or is to be implied regarding the accuracy or completeness of this information, the results to be obtained from the use of this information or the product, the safety of this product, or the hazards related to its use. This information and product are furnished on the condition that the person receiving them shall make his own determination as to the suitability of the product for his particular purpose and on condition that he assume the risk of his use thereof.