

SAFETY DATA SHEET

Goof Off Adhesive Gunk Remover

Page: 1 of 8

Printed: 04/25/2023

Revision: 04/25/2023

Supersedes Revision: 07/14/2022

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name: Goof Off Adhesive Gunk Remover
Company Name: W. M. Barr
2105 Channel Avenue
Memphis, TN 38113
Web site address: www.wmbarr.com
Emergency Contact: 3E 24 Hour Emergency Contact (800)451-8346
Information: W.M. Barr Customer Service (800)398-3892
Intended Use: Adhesive remover
Product Code: FG790, FG791AM, FG795, FG796

2. HAZARDS IDENTIFICATION

Skin Corrosion/Irritation, Category 2



GHS Signal Word: Warning

GHS Hazard Phrases:

GHS Precautionary Phrases: P233: Keep container tightly closed.
P264: Wash hands thoroughly after handling.
P280: Wear protective gloves/protective clothing/eye protection/face protection.

GHS Response Phrases: P302+352: IF ON SKIN: Wash with plenty of soap and water.
P321: Specific treatment see the label.
P332+313: If skin irritation occurs, get medical advice/attention.

GHS Storage and Disposal Phrases: P403+235: Store in cool/well-ventilated place.
P501: Dispose of contents/container according to local, state and federal regulations.

OSHA Regulatory Status: This material is classified as not hazardous under OSHA regulations.

3. COMPOSITION/INFORMATION ON INGREDIENTS

CAS #	Hazardous Components (Chemical Name)	Concentration
112-80-1	Oleic acid {9-Octadecenoic acid (Z)-}	7.0 -13.0 %
111-76-2	Ethanol, 2-Butoxy- {Ethylene glycol n-butyl ether, (a glycol ether)}	7.0 -13.0 %
100-51-6	Benzenemethanol {Benzyl alcohol}	3.0 -7.0 %
5989-27-5	d-Limonene	0.1 -1.0 %
586-62-9	Terpinolene	0.1 -1.0 %
1310-58-3	Potassium hydroxide {Caustic potash}	0.1 -1.0 %
99-85-4	.delta.-Terpinene {1-Isopropyl-4-methyl-1,4-cyclohexadiene}	0.1 -1.0 %
99-87-6	p-Cymene {4-Isopropyltoluene}	0.1 -1.0 %
64742-47-8	Hydrotreated light distillate (petroleum, mineral spirits)	0.1 -1.0 %

Additional Chemical Information Specific percentage of composition is being withheld as a trade secret.

4. FIRST AID MEASURES

Emergency and First Aid Procedures:

Skin:

Immediately begin washing the skin thoroughly with large amounts of water and mild soap, if available, while removing contaminated clothing. Seek medical attention if irritation persists.

Eyes:

Immediately begin to flush eyes with water, remove any contact lens. Continue to flush the eyes for at least 15 minutes, then seek immediate medical attention.

Inhalation:

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention.

Ingestion:

If swallowed, do NOT induce vomiting. Seek immediate medical attention. Call a physician, hospital emergency room, or poison control center immediately. Never give anything by mouth to an unconscious person. If spontaneous vomiting is about to occur, place victim's head below knees. If victim is drowsy or unconscious, place on the left side with head down.

5. FIRE FIGHTING MEASURES

Flammability Classification: NFPA Class 3

Flash Pt: None Method Used: Setaflash Closed Cup (Rapid Setaflash)

Explosive Limits: LEL: N.D. UEL: N.D.

Autoignition Pt: N.D.

Suitable Extinguishing Media: Use carbon dioxide, dry powder, water spray, or foam.

Unsuitable Extinguishing Media: Solid streams of water may be ineffective and spread material.

Fire Fighting Instructions: Self-contained respiratory protection should be provided for fire fighters fighting fires in buildings or confined areas. Storage containers exposed to fire should be kept cool with water spray to prevent pressure build-up. Stay away from heads of containers that have been exposed to intense heat or flame.

Product does not sustain combustion.

Flammable Properties and Hazards: Flashpoint: No flash to boiling. This material does not exhibit a flashpoint per the Setaflash Closed Cup test method.

Hazardous Combustion Products: Oxides of carbon.

6. ACCIDENTAL RELEASE MEASURES

Steps To Be Taken In Case Material Is Released Or Spilled: Vapors may cause flash fire or ignite explosively.

Clean up: Keep unnecessary people away; isolate hazard area and deny entry. Stay upwind, out of low areas, and ventilate closed spaces before entering. Shut off ignition sources; keep flares, smoking or flames out of hazard area. Use non-sparking tools. Use proper bonding and grounding methods for all equipment and processes. Keep out of waterways and bodies of water. Be cautious of vapors collecting in small enclosed spaces, sewers, low lying areas, confined spaces, etc.

Small spills: Take up with sand, earth or other noncombustible absorbent material and

SAFETY DATA SHEET

Goof Off Adhesive Gunk Remover

Page: 3 of 8

Printed: 04/25/2023

Revision: 04/25/2023

Supersedes Revision: 07/14/2022

place in a plastic container where applicable.

Large spills: Dike far ahead of spill for later disposal.

Waste Disposal: Dispose in accordance with applicable local, state and federal regulations.

7. HANDLING AND STORAGE

Precautions To Be Taken in Handling: Read carefully all cautions and directions on product label before use. Since empty container retains residue, follow all label warnings even after container is empty. Dispose of empty container according to all regulations. Do not reuse this container.

Do not use this product near any source of heat or open flame, furnace areas, pilot lights, stoves, etc.

Do not use in small enclosed spaces, such as basements and bathrooms. Vapors can accumulate and explode if ignited.

Do not spread this product over large surface areas because fire and health safety risks will increase dramatically.

Precautions To Be Taken in Storing: Keep container tightly closed when not in use. Store in a cool, dry place. Do not store near flames or at elevated temperatures.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

CAS #	Partial Chemical Name	OSHA TWA	ACGIH TWA	Other Limits
112-80-1	Oleic acid {9-Octadecenoic acid (Z)-}			
111-76-2	Ethanol, 2-Butoxy- {Ethylene glycol n-butyl ether, (a glycol ether)}	PEL: 50 ppm	TLV: 20 ppm	
100-51-6	Benzenemethanol {Benzyl alcohol}			
5989-27-5	d-Limonene			
586-62-9	Terpinolene			
1310-58-3	Potassium hydroxide {Caustic potash}		CEIL: 2 mg/m ³	
99-85-4	.delta.-Terpinene {1-Isopropyl-4-methyl-1,4-cyclohexadiene}			
99-87-6	p-Cymene {4-Isopropyltoluene}			
64742-47-8	Hydrotreated light distillate (petroleum, mineral spirits)		TLV: 200 mg/m ³	

SAFETY DATA SHEET

Goof Off Adhesive Gunk Remover

Page: 4 of 8

Printed: 04/25/2023

Revision: 04/25/2023

Supersedes Revision: 07/14/2022

Respiratory Equipment (Specify Type):	<p>For use in areas with inadequate ventilation or fresh air, wear a properly maintained and properly fitted NIOSH approved respirator for organic solvent vapors.</p> <p>For OSHA controlled work places and other regular users - Use only with adequate ventilation under engineered air control systems designed to prevent exceeding the appropriate TLV.</p> <p>A dust mask does not provide protection against vapors.</p>
Eye Protection:	<p>Safety glasses should be worn during normal handling of this material.</p> <p>Where contact with the eyes or face is likely, a faceshield or chemical splash goggles should be worn to prevent eye contact.</p>
Protective Gloves:	<p>Wear gloves with as much resistance to the chemical ingredients as possible. Glove materials such as nitrile rubber may provide protection. Glove selection should be based on chemicals being used and conditions of use. Consult your glove supplier for additional information. Gloves contaminated with product should be discarded and not reused.</p>
Other Protective Clothing:	<p>Various application methods can dictate use of additional protective safety equipment, such as impermeable aprons, etc., to minimize exposure.</p>
Engineering Controls (Ventilation etc.):	<p>Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits.</p> <p>Use only with adequate ventilation to prevent buildup of vapors. Do not use in areas where vapors can accumulate and concentrate, such as basements, bathrooms or small enclosed areas. Whenever possible, use outdoors in an open air area. If using indoors open all windows and doors and maintain a cross ventilation of moving fresh air across the work area. If strong odor is noticed or you experience slight dizziness, headache, nausea or eye-watering -- STOP -- ventilation is inadequate. Leave area immediately and move to fresh air.</p>
Work/Hygienic/Maintenance Practices:	<p>Wash hands thoroughly after use and before eating, drinking, smoking, or using the restroom.</p> <p>Do not eat, drink, or smoke in the work area.</p> <p>Discard any clothing or other protective equipment that cannot be decontaminated.</p> <p>Facilities storing or handling this material should be equipped with an emergency eyewash and safety shower.</p>

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical States:	[] Gas [X] Liquid [] Solid
Appearance and Odor:	Clear orange gel with orange odor. Odor threshold not determined.
pH:	7 - 7.4
Melting Point:	N.D.
Boiling Point:	> 37.70 C
Flash Pt:	None Method Used: Setaflash Closed Cup (Rapid Setaflash)
Evaporation Rate:	< 1 (BuAC=1)

SAFETY DATA SHEET

Goof Off Adhesive Gunk Remover

Page: 5 of 8

Printed: 04/25/2023

Revision: 04/25/2023

Supersedes Revision: 07/14/2022

Flammability (solid, gas):	
Explosive Limits:	LEL: N.D. UEL: N.D.
Vapor Pressure (vs. Air or mm Hg):	N.D.
Vapor Density (vs. Air = 1):	> 1 Air = 1
Specific Gravity (Water = 1):	0.952 - 0.976
Density:	7.92 - 8.12 LB/GL
Solubility in Water:	Miscible
Saturated Vapor Concentration:	N.D.
Octanol/Water Partition Coefficient:	N.D.
Percent Volatile:	88.82 % by weight.
VOC / Volume:	189.2400 G/L
HAP / Volume:	NE
Autoignition Pt:	N.D.
Decomposition Temperature:	N.D.
Viscosity:	400 - 2600 CPS
a_fld_hdr[9]:	ND = Not determined NE = Not established

Information with regard to primary physical hazard:

10. STABILITY AND REACTIVITY

Reactivity:	None known
Stability:	Unstable [] Stable [X]
Conditions To Avoid - Instability:	None known
Incompatibility - Materials To Avoid:	Oxidizers, strong acids
Hazardous Decomposition or Byproducts:	Can include aldehydes, ketones, organic acids, oxides of citrus terpenes
Possibility of Hazardous Reactions:	Will occur [] Will not occur [X]
Conditions To Avoid - Hazardous Reactions:	None known

SAFETY DATA SHEET

Goof Off Adhesive Gunk Remover

11. TOXICOLOGICAL INFORMATION

Toxicological Information: This product has not been tested as a whole. Refer to section 2 for acute and chronic effects.

CAS# 111-76-2:
 Acute toxicity, LC50, Inhalation, Rat, 450.0 PPM, 4 H.
 Result:
 Behavioral: Ataxia.
 Nutritional and Gross Metabolic: Weight loss or decreased weight gain.
 - Toxicology and Applied Pharmacology, Academic Press, Inc., 1 E. First St., Duluth, MN 55802, Vol/p/yr: 68,405, 1983

Acute toxicity, LD50, Skin, Species: Rabbit, 220.0 MG/KG.
 Result:
 Effects on Embryo or Fetus: Extra embryonic structures (e.g., placenta, umbilical cord).
 Effects on Embryo or Fetus: Other effects to embryo.
 Specific Developmental Abnormalities: Musculoskeletal system.
 - Dow Chemical Company Reports., Dow Chemical USA, Health and Environment Research, Toxicology Research Lab, Midland, MI 48640, Vol/p/yr: MSD-46,

Acute toxicity, LD50, Oral, Rat, 250.0 mg/kg.
 Result:
 Lungs, Thorax, or Respiration: Changes in pulmonary vascular resistance.

Standard Draize Test, Eyes, Species: Rabbit, 100.0 MG, Severe.
 Result:
 Effects on Newborn: Apgar score (human only).
 Effects on Newborn: Other neonatal measures or effects.
 Effects on Newborn: Drug dependency.
 - American Journal of Ophthalmology., Ophthalmic Pub. Co., 435 N. Michigan Ave., Suite 1415, Chicago, IL 60611, Vol/p/yr: 29,1363, 1946

Carcinogenicity/Other Information: IARC 3: Not Classifiable as to Carcinogenicity in Humans.
 ACGIH A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans

CAS #	Hazardous Components (Chemical Name)	NTP	IARC	ACGIH	OSHA
112-80-1	Oleic acid {9-Octadecenoic acid (Z)-}				
111-76-2	Ethanol, 2-Butoxy- {Ethylene glycol n-butyl ether, (a glycol ether)}		3	A3	
100-51-6	Benzenemethanol {Benzyl alcohol}				
5989-27-5	d-Limonene		3		
586-62-9	Terpinolene				
1310-58-3	Potassium hydroxide {Caustic potash}				
99-85-4	.delta.-Terpinene {1-Isopropyl-4-methyl-1,4-cyclohexadiene}				
99-87-6	p-Cymene {4-Isopropyltoluene}				
64742-47-8	Hydrotreated light distillate (petroleum, mineral spirits)			A4	

SAFETY DATA SHEET

Goof Off Adhesive Gunk Remover

12. ECOLOGICAL INFORMATION

General Ecological Information: This product has not been tested as a whole.

13. DISPOSAL CONSIDERATIONS

Waste Disposal Method: Dispose of in accordance with local, state, and federal laws.

Do not place material in general trash.

Do not allow material to enter bodies of water or sewers.

14. TRANSPORT INFORMATION

LAND TRANSPORT (US DOT):

DOT Proper Shipping Name: Not Regulated.

DOT Hazard Class:

UN/NA Number:

15. REGULATORY INFORMATION

EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists

CAS #	Hazardous Components (Chemical Name)	S. 302 (EHS)	S. 304 RQ	S. 313 (TRI)
112-80-1	Oleic acid {9-Octadecenoic acid (Z)-}	No	No	No
111-76-2	Ethanol, 2-Butoxy- {Ethylene glycol n-butyl ether, (a glycol ether)}	No	No	Yes-Cat. N230
100-51-6	Benzenemethanol {Benzyl alcohol}	No	No	No
5989-27-5	d-Limonene	No	No	No
586-62-9	Terpinolene	No	No	No
1310-58-3	Potassium hydroxide {Caustic potash}	No	Yes NA	No
99-85-4	.delta.-Terpinene {1-Isopropyl-4-methyl-1,4-cyclohexadiene}	No	No	No
99-87-6	p-Cymene {4-Isopropyltoluene}	No	No	No
64742-47-8	Hydrotreated light distillate (petroleum, mineral spirits)	No	No	No

CAS #	Hazardous Components (Chemical Name)	Other US EPA or State Lists
112-80-1	Oleic acid {9-Octadecenoic acid (Z)-}	TSCA: Inventory
111-76-2	Ethanol, 2-Butoxy- {Ethylene glycol n-butyl ether, (a glycol ether)}	CAA HAP, ODC: Yes - Cat. TSCA: Inventory
100-51-6	Benzenemethanol {Benzyl alcohol}	TSCA: Inventory
5989-27-5	d-Limonene	TSCA: Inventory
586-62-9	Terpinolene	TSCA: Inventory
1310-58-3	Potassium hydroxide {Caustic potash}	TSCA: Inventory
99-85-4	.delta.-Terpinene {1-Isopropyl-4-methyl-1,4-cyclohexadiene}	TSCA: Inventory
99-87-6	p-Cymene {4-Isopropyltoluene}	TSCA: Inventory
64742-47-8	Hydrotreated light distillate (petroleum, mineral spirits)	TSCA: Inventory

SAFETY DATA SHEET

Goof Off Adhesive Gunk Remover

Additional Regulatory Information

This product is regulated by the United States Consumer Product Safety Commission and is subject to certain labeling requirements under the Federal Hazardous Substances Act. These requirements differ from the classification criteria and hazard information required for safety data sheets (SDS). The product label also includes other important information, including directions for use, and should always be read in its entirety prior to using the product.

16. OTHER INFORMATION

Revision Date: 04/25/2023**Previous revision:** 07/14/2022**Preparer Name:** EHS Department**Additional Information About****This Product:****Company Policy or****Disclaimer:**

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, state and local laws and regulations.